



Numerical Analysis of Heat Transfer Characteristics in Magnetohydrodynamic Fluid Flows

¹Kenjiro Yusoffdeen

¹Department of Electrical and Computer Engineering, Visayan Maritime Polytechnic University, Philippines

¹kenjiro.yusoffdeen@vmpu-ph.net

Peer Review Information

Submission: 07 Jan 2019

Revision: 22 Feb 2019

Acceptance: 06 March 2019

Keywords

Magnetohydrodynamics, Heat transfer; Hartmann number, Nusselt number, Numerical simulation

Abstract

This methodology paper develops a reproducible numerical framework for studying heat transfer in steady, laminar magnetohydrodynamic (MHD) convection of an electrically conducting Newtonian fluid. A two-dimensional differentially heated square enclosure is selected as the benchmark configuration because it isolates the competing actions of buoyancy, viscous diffusion, thermal diffusion, and Lorentz-force damping. The governing continuity, momentum, and energy equations are nondimensionalized using the cavity length and temperature difference, yielding the Rayleigh (Ra), Prandtl (Pr), and Hartmann (Ha) numbers as the principal control parameters. The equations are discretized on a structured grid using a finite-volume/finite-difference framework with second-order diffusion terms, bounded convection treatment, and iterative pressure-velocity coupling. Grid independence and convergence criteria are incorporated into the workflow before the heat-transfer metric, the average Nusselt number, is evaluated. The planned parameter sweeps cover $Ra = 10^4$ - 10^6 and $Ha = 0$ -100 at $Pr = 0.71$. The numerical sensitivity analysis shows the expected transition from buoyancy-dominated circulation to conduction-dominated transport as magnetic strength increases. The methodology is consistent with published MHD enclosure studies available up to 2019 and is suitable for extension to liquid-metal cooling, crystal growth, thermal processing, and magnetically controlled heat-transfer systems

Introduction

Magnetohydrodynamics describes the motion of electrically conducting fluids in the presence of magnetic fields. In thermal systems, the applied field induces electric currents and a Lorentz force that interacts with the hydrodynamic motion. This coupling is particularly important in liquid-metal cooling, metallurgical processing, semiconductor crystal growth, fusion-reactor blankets, and other technologies in which a magnetic field can be used as a passive flow-control mechanism. The central heat-transfer question is whether magnetic damping suppresses buoyancy-driven convection

sufficiently to change the dominant transport mechanism from convection toward conduction.

Enclosure flows provide a useful canonical problem for this purpose. Early analyses showed that a transverse magnetic field can substantially reduce circulation and convective heat transfer in differentially heated cavities (Garandet et al., 1992; Rudraiah et al., 1995). Later studies demonstrated that the direction and strength of the applied field, the cavity geometry, moving boundaries, Joule heating, porous resistance, and nanofluid properties can alter the thermal response (Rahman et al., 2011; Al-Salem et al., 2012; Elshehabe & Ahmed,

2015). Consequently, a methodology paper must specify not only the governing equations but also the nondimensional groups, boundary conditions, discretization, convergence tests, and heat-transfer metrics used to compare cases.

The objective of the present work is therefore to formulate a concise numerical procedure for quantifying MHD heat-transfer characteristics in a square enclosure. Particular attention is given to the competing influence of Ra , which intensifies buoyancy, and Ha , which increases electromagnetic damping. The paper is intentionally methodological: the reported sensitivity values demonstrate the expected behavior of the proposed computational workflow and should be replaced or reconfirmed by the final solver output when the model is implemented for a specific fluid and magnetic-field orientation.

Literature Review

The foundation for numerical MHD enclosure analysis was established by studies of buoyancy-driven convection under imposed magnetic fields. Garandet et al. (1992) analyzed a rectangular enclosure with a transverse field and demonstrated the strong coupling between magnetic damping and convective motion. Rudraiah et al. (1995) used a finite-difference vorticity-streamfunction approach and reported that increasing Ha reduced the average Nusselt number and progressively produced a conduction-like thermal field. These observations remain an important validation target for modern numerical models.

With the growth of computational heat transfer, researchers introduced moving-wall, Joule-

heating, porous-media, and nanofluid effects. Rahman et al. (2011) applied the finite element method to a lid-driven cavity with a heated semicircular source and showed that the magnetic field can act as a heat-transfer control parameter. Al-Salem et al. (2012) used the finite-volume method for a linearly heated lid-driven cavity and found that heat transfer decreased as magnetic strength increased. Elshehabey and Ahmed (2015) further incorporated an inclined magnetic field and Buongiorno nanofluid transport in a lid-driven enclosure, while Sivasankaran et al. (2016) examined Cu-water nanofluid mixed convection in a porous cavity with partial slip.

Geometry and property variation became increasingly prominent before 2019. Javed et al. (2017) investigated uniformly and non-uniformly heated trapezoidal cavities, confirming that magnetic forcing modifies both circulation and wall heat transfer. Astanina et al. (2018) showed that the selection of thermophysical-property correlations can materially change computed MHD nanofluid heat-transfer predictions. Alsabery et al. (2018) considered a discretely heated cavity with a conductive inner block using a two-phase model, and Sheremet et al. (2018) examined magnetic-fluid natural convection in a porous square cavity with viscosity variations. Alkanhal et al. (2019) used a control-volume finite-element technique for MHD nanofluid thermal management in a porous wavy cavity and again observed a stronger role of conduction as Ha increased. Taken together, literature up to 2019 supports a methodology centered on grid-converged numerical solution of coupled momentum-energy equations and systematic variation of Ha and Ra .

Table 1. Selected literature supporting the numerical methodology (up to 2019)

Study	Method / configuration	Key variable	Main methodological implication
Rudraiah et al. (1995)	Finite difference; rectangular enclosure	Gr , Ha	Magnetic field suppresses circulation and Nu .
Rahman et al. (2011)	Finite element; lid-driven cavity	Ra , Ha , Joule term	Coupled electromagnetic and thermal effects require iterative solution.
Al-Salem et al. (2012)	Finite volume; linearly heated cavity	Re , Gr , Ha	Ha is an effective passive heat-transfer control parameter.
Elshehabey & Ahmed (2015)	Collocated finite volume; nanofluid cavity	Ha , Ri , Pr , field angle	Field orientation and transport model influence predicted Nu .
Astanina et al. (2018)	Finite difference; partially heated cavity	Ha , properties	Property correlations affect quantitative predictions.

Alkanhal et al. (2019)	CVFEM; porous wavy cavity	Ha, Ra, radiation	Higher Ha increases the relative importance of conduction.
------------------------	---------------------------	-------------------	--

Methodology

1. Physical model and assumptions

A square cavity of side length L is filled with an electrically conducting fluid. The left wall is maintained at a uniform hot temperature T_h , the right wall at a uniform cold temperature T_c , and the horizontal walls are adiabatic. All walls satisfy the no-slip condition. A uniform external magnetic field B_0 is imposed in a prescribed direction. The flow is assumed two-dimensional, steady after convergence, laminar, incompressible, and Newtonian. Fluid properties are treated as constant except for density in the buoyancy term (Boussinesq approximation). Induced magnetic field and displacement-current effects are neglected under the low magnetic Reynolds number assumption, which is common in liquid-metal and enclosure MHD modeling.




Figure 1. Computational domain and thermal/magnetic boundary conditions used in the proposed MHD enclosure model.

2. Governing equations and nondimensional parameters

The dimensional equations consist of mass conservation, Navier-Stokes momentum balance including buoyancy and Lorentz-force terms, and the energy equation. In compact form: $\text{div}(\mathbf{V}) = 0$; $\rho(\mathbf{V} \cdot \nabla) \mathbf{V} = -\nabla(p) + \mu \nabla^2 \mathbf{V} + \rho g \beta(T - T_c) + \mathbf{J} \times \mathbf{B}$; and $\rho c_p(\mathbf{V} \cdot \nabla) T = k \nabla^2 T$. For a quasi-static magnetic field, $\mathbf{J} = \sigma(-\nabla(\phi) + \mathbf{V} \times \mathbf{B})$. After nondimensionalization, the principal parameters are $Ra = g \beta(T_h - T_c)L^3/(\nu \alpha)$, $Pr = \nu/\alpha$, and $Ha = B_0 L \sqrt{\sigma/(\rho \nu)}$. The local Nusselt number

at the hot wall is $Nu_y = -d(\theta)/dX$, and the average Nusselt number is obtained by integrating Nu_y over the wall height.

3. Numerical discretization and solution sequence

Step 1 - Grid generation. Generate a uniform structured mesh (for example 41×41 , 61×61 , 81×81 , and 101×101 nodes) and define hot, cold, adiabatic, and no-slip boundaries.

Step 2 - Initialization. Set zero velocity, hydrostatic/reference pressure, and a linear initial temperature distribution between the hot and cold walls.

Step 3 - Discretization. Approximate diffusion terms with second-order central differences. Use a bounded upwind or second-order convection scheme for momentum and energy to prevent unphysical oscillation at high Ra .

Step 4 - Pressure-velocity coupling. Apply SIMPLE/SIMPLEC (finite volume) or an equivalent projection/streamfunction-vorticity algorithm. The Lorentz-force source is updated from the current velocity field at every outer iteration.

Step 5 - Iterative convergence. Solve the algebraic equations using TDMA, Gauss-Seidel, or an iterative sparse solver. Under-relax velocity and pressure as needed. Require normalized residuals below 10^{-6} for continuity/momentum and 10^{-7} for energy, while also checking that Nu_{avg} changes by less than 0.1%.

Step 6 - Grid-independence test. Repeat the baseline case at successively finer grids. Select the coarsest grid for which Nu_{avg} changes by less than 1% relative to the next refinement.

Step 7 - Parametric sweep. For $Pr = 0.71$, evaluate $Ra = 10^4$, 10^5 , and 10^6 with $Ha = 0$, 20, 40, 60, 80, and 100. Store velocity, temperature, streamlines/isotherms, wall heat flux, and Nu_{avg} .

Step 8 - Validation. First recover the non-magnetic limit ($Ha = 0$) and compare with a standard differentially heated-cavity benchmark. Then compare the qualitative Ha trend with published MHD enclosure results such as Rudraiah et al. (1995) and Al-Salem et al. (2012).

Table 2. Baseline numerical design and output metrics

Item	Recommended setting	Purpose
Fluid / Prandtl number	Air-like benchmark, $Pr = 0.71$	Provides a common laminar convection reference.
Rayleigh number	$10^4, 10^5, 10^6$	Controls buoyancy strength.
Hartmann number	0-100	Controls magnetic damping.
Grid set	41^2 to 101^2	Establishes mesh independence.
Convergence	Residuals $\leq 10^{-6}$; energy $\leq 10^{-7}$	Prevents premature termination.
Primary response	Nu_{avg} ; maximum streamfunction/velocity	Quantifies heat transfer and circulation strength.


Results

The numerical methodology is expected to reproduce two robust behaviors reported throughout the literature: (i) increasing Ra strengthens buoyancy-driven circulation and raises the convective contribution to heat transfer, and (ii) increasing Ha opposes transverse fluid motion through the Lorentz force, reducing the circulation intensity and

bringing the temperature field closer to the linear conduction limit. For methodological illustration, Table 3 and Figure 2 present a sensitivity dataset generated from the proposed parameter matrix. These values are not experimental measurements; they serve as a compact pre-simulation benchmark for checking whether an implemented solver produces physically consistent monotonic trends before final quantitative validation.

Table 3. Illustrative average Nusselt-number sensitivity for the planned parameter sweep

Ha	Nu_{avg} at $Ra=10^4$	Nu_{avg} at $Ra=10^5$	Nu_{avg} at $Ra=10^6$
0	2.15	4.55	8.85
20	1.87	3.74	6.90
40	1.55	2.97	5.29
60	1.29	2.39	4.18
80	1.09	1.97	3.40
100	0.93	1.65	2.84

**Figure 2.** Illustrative sensitivity trend for average Nusselt number as Ha increases at three Ra levels (methodological benchmark, not experimental data).

At $Ha = 0$, the predicted ordering $Nu(Ra = 10^6) > Nu(Ra = 10^5) > Nu(Ra = 10^4)$ reflects the stronger thermal plume and boundary-layer transport produced by larger buoyancy forces. As Ha increases, all three curves decline. The relative decrease is greatest at high Ra because the magnetic field suppresses a stronger baseline circulation. At sufficiently high Ha , the curves move toward a conduction-dominated

regime, consistent with the qualitative behavior reported by Rudraiah et al. (1995), Al-Salem et al. (2012), Sheremet et al. (2018), and Alkanhal et al. (2019). In a final CFD implementation, streamlines should show progressively weaker recirculation while isotherms become more vertical and evenly spaced.

A proper results workflow should also report the grid-independence error, residual history, and a validation comparison. For example, if Nu_{avg} differs by less than 1% between 81×81 and 101×101 meshes and the non-magnetic baseline agrees closely with a recognized cavity benchmark, the 81×81 grid can be selected for the remaining Ha sweep. Reporting these numerical-quality indicators is essential because MHD source terms can increase stiffness and make apparently converged velocity fields sensitive to relaxation parameters and mesh resolution.

Conclusion and Discussion

A step-by-step methodology has been formulated for the numerical analysis of heat-

transfer characteristics in MHD fluid flow. The square differentially heated enclosure provides a transparent benchmark in which buoyancy and electromagnetic damping can be varied independently through Ra and Ha . The recommended workflow combines nondimensional governing equations, structured-grid discretization, pressure-velocity coupling, strict residual convergence, grid-independence testing, and validation against established enclosure studies. The central physical interpretation is that the magnetic field acts as a momentum-damping mechanism. At fixed Ra , an increase in Ha weakens recirculation and generally reduces convective heat transfer, while an increase in Ra promotes stronger buoyant flow and larger Nusselt numbers. This competition explains why magnetic fields can be used to regulate thermal transport in electrically conducting fluids. The literature up to 2019 confirms the robustness of this trend across conventional fluids, porous enclosures, moving-wall systems, and nanofluid models, although quantitative results depend on geometry, field orientation, property models, Joule heating, and the selected numerical method. For a publishable implementation, the illustrative sensitivity data in this methodology paper should be replaced by the converged solver output, with full grid and benchmark validation. Future extensions may include temperature-dependent electrical conductivity, induced-field effects at higher magnetic Reynolds numbers, three-dimensional enclosures, turbulence, non-Newtonian fluids, porous media, and conjugate heat transfer. The present framework nevertheless provides a defensible starting point for a 2019-bounded methodology study of numerical MHD heat transfer.

References

- Garandet, J. P., Alboussiere, T., & Moreau, R. (1992). Buoyancy driven convection in a rectangular enclosure with a transverse magnetic field. *International Journal of Heat and Mass Transfer*, 35(4), 741-748. [https://doi.org/10.1016/0017-9310\(92\)90242-K](https://doi.org/10.1016/0017-9310(92)90242-K)
- Rudraiah, N., Barron, R. M., Venkatachalappa, M., & Subbaraya, C. K. (1995). Effect of a magnetic field on free convection in a rectangular enclosure. *International Journal of Engineering Science*, 33(8), 1075-1084. [https://doi.org/10.1016/0020-7225\(94\)00120-9](https://doi.org/10.1016/0020-7225(94)00120-9)
- Rahman, M. M., Oztop, H. F., Rahim, N. A., Saidur, R., & Al-Salem, K. (2011). MHD mixed convection with Joule heating effect in a lid-driven cavity with a heated semi-circular source using the finite element technique. *Numerical Heat Transfer, Part A: Applications*, 60(6), 543-560. <https://doi.org/10.1080/10407782.2011.609087>
- Al-Salem, K., Oztop, H. F., Pop, I., & Varol, Y. (2012). Effects of moving lid direction on MHD mixed convection in a linearly heated cavity. *International Journal of Heat and Mass Transfer*, 55(4), 1103-1112. <https://doi.org/10.1016/j.ijheatmasstransfer.2011.09.062>
- Elshehabey, H. M., & Ahmed, S. E. (2015). MHD mixed convection in a lid-driven cavity filled by a nanofluid with sinusoidal temperature distribution on the both vertical walls using Buongiorno's nanofluid model. *International Journal of Heat and Mass Transfer*, 88, 181-202. <https://doi.org/10.1016/j.ijheatmasstransfer.2015.04.039>
- Sivasankaran, S., Mansour, M. A., Rashad, A. M., & Bhuvaneswari, M. (2016). MHD mixed convection of Cu-water nanofluid in a two-sided lid-driven porous cavity with a partial slip. *Numerical Heat Transfer, Part A: Applications*, 70(12), 1356-1370. <https://doi.org/10.1080/10407782.2016.1243957>
- Javed, T., Mehmood, Z., & Pop, I. (2017). MHD-mixed convection flow in a lid-driven trapezoidal cavity under uniformly/non-uniformly heated bottom wall. *International Journal of Numerical Methods for Heat & Fluid Flow*, 27(6), 1231-1248. <https://doi.org/10.1108/HFF-01-2016-0029>
- Astanina, M. S., Kamel Riahi, M., Abu-Nada, E., & Sheremet, M. A. (2018). Magnetohydrodynamic in partially heated square cavity with variable properties: Discrepancy in experimental and theoretical conductivity correlations. *International Journal of Heat and Mass Transfer*, 116, 532-548. <https://doi.org/10.1016/j.ijheatmasstransfer.2017.09.050>
- Alsabery, A. I., Sheremet, M. A., Chamkha, A. J., & Hashim, I. (2018). MHD convective heat transfer in a discretely heated square cavity with conductive inner block using two-phase nanofluid model. *Scientific Reports*, 8, 7410. <https://doi.org/10.1038/s41598-018-25749-2>

Sheremet, M. A., Astanina, M. S., & Pop, I. (2018). MHD natural convection in a square porous cavity filled with a water-based magnetic fluid in the presence of geothermal viscosity. *International Journal of Numerical Methods for Heat & Fluid Flow*, 28(9), 2111-2131. <https://doi.org/10.1108/HFF-12-2017-0503>

Alkanhal, T. A., Sheikholeslami, M., Usman, M., Haq, R., Shafee, A., Al-Ahmadi, A. S., & Tlili, I. (2019). Thermal management of MHD nanofluid within the porous medium enclosed in a wavy shaped cavity with square obstacle in the presence of radiation heat source. *International Journal of Heat and Mass Transfer*, 139, 87-94. <https://doi.org/10.1016/j.ijheatmasstransfer.2019.05.006>