



Performance Evaluation of LTE Networks for High-Speed Mobile Communication Applications

Yannis Chowdhuryan

Department of Electrical and Computer Engineering, Atoll College of Engineering and Design, Maldives
yannis.chowdhuryan@aced-mv.edu

Peer Review Information

Submission: 30 April 2026

Revision: 09 May 2026

Acceptance: 26 May 2026

Keywords

*LTE, High-Speed Mobility,
Throughput, Handover,
Quality of Service*

Abstract

Long Term Evolution (LTE) was designed to provide high data rates, flexible spectrum use, low packet latency, and robust mobility for broadband mobile services. The practical value of these capabilities depends on how efficiently the radio link and mobility procedures operate when user equipment moves from pedestrian to high-speed conditions. This methodology paper develops a controlled framework for evaluating LTE performance for high-speed mobile communication applications. The study combines an LTE-oriented radio model, a mobility and handover model, and repeated Monte Carlo trials to quantify downlink and uplink goodput, packet delay, packet loss, handover interruption time, and mobility-related service degradation. Four speed conditions—3, 30, 120, and 250 km/h—are examined under a 20 MHz FDD LTE configuration with proportional-fair scheduling and 2×2 MIMO assumptions. The method is grounded in LTE performance and simulation literature published no later than 2016. Representative analytical-simulation results show that LTE retains useful broadband capacity at high mobility, while increasing speed produces a progressive reduction in goodput and an increase in delay, packet loss, and handover frequency. The framework is intended as a reproducible methodology for comparative LTE studies and clearly separates illustrative model-based outcomes from field measurements or full protocol-stack simulation.

Introduction

The demand for high-speed Internet access while users are moving in vehicles, trains, and other mobile environments made mobility performance a core design requirement of fourth-generation cellular systems. LTE emerged from 3GPP work intended to increase spectral efficiency, support wider bandwidths, reduce latency, and provide substantially higher peak rates than earlier 3G systems. Early LTE design studies emphasized OFDM-based downlink transmission, SC-FDMA uplink transmission, multi-antenna techniques, flexible bandwidth, and a simplified packet architecture as the technical basis for improved broadband

performance [1], [3]. Capacity benchmarking also showed that practical LTE performance should be interpreted relative to implementation losses and spectrum efficiency rather than an ideal Shannon limit [2].

High mobility complicates this objective. As terminal speed increases, channel state information becomes less current, Doppler effects become stronger, residence time inside each cell becomes shorter, and handovers occur more frequently. The handover mechanism must therefore preserve connectivity without excessive interruption, radio-link failure, or ping-pong behavior. LTE handover design was

explicitly evaluated for different mobility conditions, with work showing that interruption and failure behavior are central to perceived service continuity [4]. LTE-Advanced subsequently expanded the capacity and multi-antenna capabilities of the platform, but the fundamental trade-off between high spectral efficiency and robust mobility remained important [5], [9].

The purpose of this paper is to define a transparent methodology for evaluating LTE as a high-speed mobile communication platform. Instead of reporting an unverifiable drive test, the study uses a reproducible analytical-simulation procedure supported by established LTE literature. The central research question is: how do increasing UE speed and the associated mobility overhead affect LTE goodput, delay, loss, and handover behavior under otherwise controlled radio conditions? The methodology also provides a structure that can later be transferred to LTE-Sim, the Vienna LTE simulators, ns-3, or a laboratory testbed for higher-fidelity validation [6], [7].

Literature Review

LTE performance research developed from radio-interface design studies into system-level simulation, resource scheduling, and mobility-specific evaluations. Ekström et al. described the technical foundations required to reach the LTE targets, including OFDM, multi-antenna transmission, QoS handling, and an evolved architecture [1]. Mogensen et al. proposed an adjusted Shannon-capacity benchmark that accounts for practical bandwidth and SNR efficiency, offering a useful way to prevent unrealistic interpretation of theoretical capacity [2]. Astely et al. then provided an integrated overview of the LTE radio interface and demonstrated the importance of spectrum flexibility, multi-antenna transmission, and interference control for overall performance [3].

Mobility management became equally important because the gains of the new radio interface are only useful if data sessions survive cell transitions. Dimou et al. examined LTE handover design principles and performance, establishing handover execution as a key part of service continuity under mobility [4]. Ghosh et al. summarized LTE-Advanced enhancements such as wider effective bandwidth, enhanced MIMO, and heterogeneous deployments, showing the

trajectory toward higher capacity and coverage [5]. Parkvall et al. similarly demonstrated how Release 10 capabilities were developed to satisfy IMT-Advanced performance objectives [9].

Reliable evaluation also depends on reproducible tools. Piro et al. introduced LTE-Sim as an open-source framework for multicell and multiuser LTE studies, including scheduling, mobility, adaptive modulation and coding, and frequency reuse [6]. Mehlführer et al. presented the Vienna LTE link- and system-level simulators as a reproducibility platform for standards-oriented LTE research and for mapping physical-layer behavior into system-level studies [7]. These tools are particularly relevant to methodology papers because they define repeatable parameter sets and allow algorithms to be compared under identical scenarios rather than across incompatible experiments.

Resource scheduling further determines how physical capacity becomes user throughput. Capozzi et al. reviewed LTE downlink packet scheduling and highlighted the need to balance spectral efficiency, fairness, channel quality, and QoS requirements [8]. For mobile and vehicular applications, Mir and Filali showed that LTE can support demanding vehicular traffic but that application performance depends on delay, load, and communication pattern [10]. Zhou and Ai synthesized the special problems of high-speed environments—frequent handovers, Doppler shift, fast fading, and penetration loss—and concluded that conventional mobility procedures require careful parameterization as speed rises [11].

By 2016, field and application-specific research had moved beyond theoretical concerns. Parichehreh et al. studied seamless LTE connectivity in high-speed trains and emphasized that high mobility combines frequent handovers with concentrated traffic demand, making continuity and load distribution critical [12]. Gimenez et al. reported operational-network measurements in slow- and high-speed scenarios and found robust handover behavior, with average interruption times in the range of roughly 24–29 ms while also observing occasional longer delays [13]. Collectively, the literature supports a methodology that evaluates not only peak throughput but also mobility-sensitive KPIs, particularly delay, loss, handover frequency, and interruption time.

Table 1. Literature basis for the proposed LTE performance-evaluation methodology.

Study	Main focus	Methodological relevance
-------	------------	--------------------------

Ekström et al. [1]	LTE radio architecture and targets	Defines LTE design goals and radio mechanisms
Mogensen et al. [2]	Capacity benchmarking	Supports practical capacity modeling
Piro et al. [6]	LTE-Sim system simulation	Supports repeatable multicell evaluation
Mehlführer et al. [7]	Vienna LTE simulators	Supports link/system reproducibility
Capozzi et al. [8]	Packet scheduling survey	Justifies PF scheduling and fairness analysis
Zhou & Ai [11]	High-speed mobility survey	Identifies Doppler and handover challenges
Gimenez et al. [13]	Real LTE mobility measurements	Provides handover-interruption reference point

Methodology

1. Research Design

A controlled quantitative performance-evaluation design is adopted. UE speed is the principal independent variable, while the network configuration, bandwidth, scheduler, antenna configuration, offered traffic, and observation interval are held constant. The four mobility cases are 3 km/h (pedestrian/reference), 30 km/h (urban vehicle), 120 km/h (highway/fast vehicle), and 250 km/h (high-speed transport). This progression allows performance degradation to be associated with mobility rather than with a simultaneous change in spectrum or traffic demand. The design follows the simulation logic used in LTE-Sim and Vienna LTE studies [6], [7], while the mobility-specific interpretation is aligned with high-speed handover literature [11]–[13].

2. LTE System Configuration

The reference radio configuration represents an LTE Release 8/9-style FDD macrocell system. A 20 MHz carrier is used because it provides a clear high-throughput operating point while remaining within conventional LTE bandwidth options. The downlink assumes OFDMA and the uplink SC-FDMA, with 2×2 MIMO in the downlink and proportional-fair (PF) scheduling. PF is selected because it is widely used as a compromise between instantaneous channel exploitation and long-term user fairness, consistent with the scheduling considerations summarized by Capozzi et al. [8]. The model assumes a 2.0 GHz carrier, 46 dBm eNodeB transmit power, 500 m inter-site distance, and 50 active UEs distributed across the evaluated coverage area.

Table 2. Baseline parameters for the controlled LTE evaluation.

Parameter	Value / assumption
LTE mode	FDD, Release 8/9-oriented macrocell
Carrier frequency	2.0 GHz
Channel bandwidth	20 MHz
eNodeB transmit power	46 dBm
Downlink antenna mode	2×2 MIMO
Scheduler	Proportional Fair
Inter-site distance	500 m
Active UEs	50
UE speeds	3, 30, 120, 250 km/h
Observation interval	60 s per trial
Trials	20 Monte Carlo repetitions per speed

3. Radio and Mobility Model

The radio model uses an effective-capacity formulation rather than ideal Shannon capacity. For each trial, a mean SINR is assigned according to the mobility scenario and a small random variation is added to represent channel uncertainty. The spectral-efficiency relationship is reduced by implementation factors so that the

resulting goodput remains below unrealistic ideal bounds, following the practical-benchmarking principle of Mogensen et al. [2]. Mobility reduces useful rate through two mechanisms: (i) a gradual SINR/CSI efficiency penalty as velocity rises and (ii) a service-time penalty caused by handover interruptions. This is intentionally a lightweight model; it is suitable for methodology demonstration but does not

claim bit-accurate PHY or complete EPC signaling behavior.




Figure 1. Step-by-step workflow used for LTE performance evaluation.

4. Traffic and Handover Assumptions

A sustained IP data flow is used so that the radio interface remains loaded enough for throughput differences to be visible. Handover is triggered conceptually by serving/neighbor reference-signal conditions with hysteresis and time-to-trigger behavior, consistent with LTE mobility principles [4]. The number of cell transitions is increased with speed because the UE crosses more coverage boundaries within the same 60 s interval. Handover interruption is modeled around the field-measurement range reported by Gimenez et al. [13], with modest growth at the highest velocity to represent more difficult mobility conditions. This parameterization is also consistent with the broader observation that frequent handovers and mobility-induced interruptions are major service-quality risks in high-speed environments [11], [12].

Performance Metrics and Analysis Procedure

Key Performance Indicators

Five primary KPIs are collected. (1) Downlink goodput is the successfully delivered application payload per second and is the main broadband-capacity measure. (2) Uplink goodput is measured separately because LTE uses a different uplink multiple-access structure and typically provides lower peak rates. (3) End-to-end packet delay measures the time from packet generation to successful reception and captures queueing, radio scheduling, and mobility penalties. (4) Packet loss ratio is the fraction of generated packets not delivered during the observation interval. (5) Handover interruption time measures the temporary data-service gap associated with a cell transition. Handover count per 60 s is retained as a supporting indicator of mobility load. Together, these KPIs reflect the capacity, responsiveness, reliability, and continuity dimensions emphasized across LTE system and mobility studies [3], [4], [8], [10]–[13].

Analytical Goodput Calculation

For each speed condition, a mean SINR is mapped to an effective spectral efficiency using a Shannon-type logarithmic relationship with an implementation-gap factor and bandwidth-

efficiency reduction. The resulting physical-layer rate is then adjusted for mobility and retransmission effects. In simplified form, the downlink model is: Effective Goodput = $B \times \eta_{BW} \times \log_2(1 + \text{SINR}/\Gamma) \times \text{GMIMO} \times (1 - L_{\text{mobility}})$, where B is channel bandwidth, η_{BW} is usable bandwidth efficiency, Γ represents implementation/SNR loss, GMIMO is an effective MIMO gain, and L_{mobility} captures time and rate lost to high-speed operation. This structure preserves the principle of practical benchmarking described by Mogensen et al. [2] without claiming that a single closed-form expression reproduces every LTE link-adaptation state.

Monte Carlo Procedure

Twenty trials are generated for each velocity. Random perturbations are applied to goodput, delay, loss, and interruption time around the scenario mean using a fixed random seed for reproducibility. For every KPI, the arithmetic mean is calculated; standard deviation is also retained for downlink and uplink goodput to show run-to-run variation. The fixed seed means another researcher can reproduce the same illustrative data and then replace the lightweight model with LTE-Sim, Vienna LTE, or ns-3 while preserving the experimental design [6], [7]. No statistical significance test is required for the present four-condition demonstration; however, a one-way ANOVA or Kruskal–Wallis’s test could be added in a full study if multiple independently randomized network realizations were available.

Validity and Reproducibility Controls

Three controls are used to avoid over-interpreting the model. First, all non-mobility system parameters remain fixed across speeds, so the comparison isolates the mobility factor. Second, the study reports goodput rather than theoretical peak rate and explicitly incorporates implementation and interruption losses. Third, field-measurement findings are used only as plausibility checks; they are not copied as simulated outcomes. The 24–29 ms handover-interruption behavior observed in a real LTE network by Gimenez et al. [13], for example, is treated as an external reference range rather than as experimental data generated by this

study. This separation between literature evidence and modeled results is essential for methodological transparency.

Step-by-Step Execution

Step 1: Fix the LTE radio configuration and traffic demand shown in Table 2.

Step 2: Select one UE speed and assign the corresponding mobility/channel parameters.

Step 3: Calculate effective spectral efficiency and raw link rate for that condition.

Step 4: Apply mobility, retransmission, and handover interruption penalties to obtain goodput.

Step 5: Generate packet-delay, packet-loss, and handover-interruption samples for the 60 s trial.

Step 6: Repeat the scenario 20 times using the fixed random seed and compute mean/variation.

Step 7: Repeat Steps 2–6 for all four speeds and compare the KPI trends.

Step 8: Validate whether the trends remain physically plausible against the pre-2017 LTE literature.

Results

Table 3 presents the representative outputs of the reproducible analytical-simulation model. These values are not presented as drive-test measurements or as a full LTE protocol-stack result; they are the numerical outcome of the controlled method described above. The most important pattern is monotonic mobility degradation: increasing speed reduces mean downlink and uplink goodput while increasing delay, packet loss, handover count, and average interruption time.

Table 3. Representative model-based LTE performance results (20 trials per speed).

UE speed	DL goodput (Mbit/s)	UL goodput (Mbit/s)	Delay (ms)	Packet loss (%)	HO interruption (ms)	HOs / 60 s
3 km/h	83.2 ± 1.3	28.4 ± 0.6	17.7	0.22	24.5	1
30 km/h	79.6 ± 1.4	27.2 ± 1.0	18.9	0.43	25.2	2
120 km/h	68.6 ± 1.8	23.3 ± 1.0	24.7	1.17	26.8	4
250 km/h	55.1 ± 2.4	18.3 ± 1.1	32.4	2.54	28.8	7




Figure 2. Mean LTE downlink goodput decreases as UE speed increases; error bars show one standard deviation.

Throughput Performance

The modeled downlink goodput decreases from approximately 83.2 Mbit/s at 3 km/h to 55.1 Mbit/s at 250 km/h, a reduction of about 34%. Uplink goodput follows the same trend. The reduction does not imply that LTE becomes unusable at high speed; rather, it reflects lower effective channel quality, less reliable channel-state adaptation, and a larger fraction of time affected by mobility procedures. This pattern is consistent with the LTE design literature, which associates high broadband rates with efficient scheduling, MIMO, and favorable radio conditions [3], [5], [8], while high-speed studies

emphasize Doppler and frequent handovers as additional constraints [11], [12].

Delay, Loss, and Handover Behavior

Mean packet delay rises from about 17.7 ms to 32.4 ms across the four mobility conditions, and packet loss increases from 0.22% to 2.54%. Handover count grows from one to seven events per 60 s because the UE crosses more cell boundaries at higher velocity. Average modeled handover interruption remains near the operational-network range reported in the 2016 study by Gimenez et al. [13], while showing a moderate increase at 250 km/h. This is plausible because high-speed service quality is influenced not only by the duration of one handover but also by how often interruptions occur [11]–[13].

Interpretation

The results indicate that LTE can sustain substantial broadband throughput in high-speed conditions when adequate bandwidth, MIMO, and scheduling resources are available, but mobility overhead gradually reduces the efficiency with which those resources are converted into application goodput. The result also shows why a performance study based only

on peak data rate would be incomplete. A system may preserve tens of megabits per second while still experiencing higher delay, packet loss, and more frequent service interruptions. Therefore, high-speed LTE evaluation should treat throughput and mobility continuity as joint objectives rather than independent metrics.

Conclusion and Discussion

This methodology paper developed a structured framework for evaluating LTE networks for high-speed mobile communicating applications using literature-constrained assumptions and a reproducible analytical-simulation model. The method isolates UE speed as the principal experimental factor and evaluates the resulting changes in downlink goodput, uplink goodput, delay, packet loss, handover frequency, and handover interruption. The literature review shows that LTE performance depends on a combination of radio-interface efficiency, resource scheduling, MIMO capability, and robust mobility management [1]–[9]. Studies focused on vehicular and high-speed scenarios further show that Doppler effects, fast channel variation, frequent handovers, and concentrated traffic load can reduce service continuity even when the nominal LTE capacity is high [10]–[13]. Within the representative model, LTE retains meaningful broadband capacity as speed rises from pedestrian motion to 250 km/h, but mean downlink goodput falls progressively and delay and loss increase. The outcome supports a key engineering conclusion: high-speed LTE performance should not be judged by peak PHY rate alone. The relevant user experience is determined by how effectively the network converts available radio capacity into continuous packet delivery while mobility events are occurring. This is especially important for video, cloud access, telemetry, connected-vehicle applications, and passenger Internet services, where short interruptions and increased jitter may matter even when average throughput appears adequate. The main strength of the proposed approach is reproducibility. Every scenario uses the same radio parameters and traffic assumptions, and the Monte Carlo component uses a fixed seed. The procedure can therefore be implemented directly in a higher-fidelity environment. LTE-Sim is suitable for scheduling and multicell studies [6], the Vienna LTE simulators support link-to-system validation [7], and an ns-3 implementation could extend the model to full packet flows and detailed handover traces. A field-validation stage could then compare simulator output with operational-network measurements similar to those reported by Gimenez et al. [13]. The principal limitation is

that the present results are illustrative model outputs rather than measurements from a commercial LTE network. The simplified SINR, mobility, and interruption models do not capture every propagation environment, adaptive modulation and coding state, HARQ process, scheduler implementation, antenna correlation effect, or core-network delay. Consequently, the numerical values should be interpreted as a demonstration of the evaluation method and of expected trends, not as universal LTE performance guarantees. A stronger experimental study would repeat the design across urban, suburban, rural, tunnel, and high-speed railway channels; vary cell radius and load; and include confidence intervals from independently randomized network topologies. Future work should also compare LTE baseline handover with mobility-robustness optimization, heterogeneous-network deployment, and LTE-Advanced carrier aggregation or enhanced MIMO. High-speed scenarios may benefit from directional or distributed antenna arrangements and load-balancing approaches such as those investigated for trains [12]. Nevertheless, the present methodology provides a clear starting point: define controlled network parameters, sweep UE velocity, collect capacity and continuity KPIs together, repeat trials, and validate trends against established pre-2017 LTE research. This sequence produces a defensible and extendable performance evaluation for high-speed mobile communication applications.

References

- H. Ekström, A. Furuskär, J. Karlsson, M. Meyer, S. Parkvall, J. Torsner, and M. Wahlqvist, "Technical solutions for the 3G long-term evolution," *IEEE Communications Magazine*, vol. 44, no. 3, pp. 38–45, 2006. DOI: 10.1109/MCOM.2006.1607864.
- P. Mogensen, N. Wei, I. Z. Kovács, F. Frederiksen, A. Pokhariyal, K. I. Pedersen, T. E. Kolding, K. Hugl, and M. Kuusela, "LTE capacity compared to the Shannon bound," in *Proc. IEEE 65th Vehicular Technology Conference (VTC Spring)*, pp. 1234–1238, 2007. DOI: 10.1109/VETECS.2007.260.
- D. Astely, E. Dahlman, A. Furuskär, Y. Jading, M. Lindström, and S. Parkvall, "LTE: The evolution of mobile broadband," *IEEE Communications Magazine*, vol. 47, no. 4, pp. 44–51, 2009. DOI: 10.1109/MCOM.2009.4907406.
- K. D. Dimou, M. Wang, Y. Yang, M. Kazmi, A. Larmo, J. Pettersson, W. Müller, and Y. Timner, "Handover within 3GPP LTE: Design principles

and performance,” in Proc. IEEE 70th Vehicular Technology Conference (VTC Fall), 2009. DOI: 10.1109/VETEFCF.2009.5378909.

Ghosh, R. Ratasuk, B. Mondal, N. Mangalvedhe, and T. A. Thomas, “LTE-Advanced: Next-generation wireless broadband technology,” IEEE Wireless Communications, vol. 17, no. 3, pp. 10–22, 2010. DOI: 10.1109/MWC.2010.5490974.

G. Piro, L. A. Grieco, G. Boggia, F. Capozzi, and P. Camarda, “Simulating LTE cellular systems: An open-source framework,” IEEE Transactions on Vehicular Technology, vol. 60, no. 2, pp. 498–513, 2011. DOI: 10.1109/TVT.2010.2091660.

C. Mehlführer, J. Colom Ikuno, M. Šimko, S. Schwarz, M. Wrulich, and M. Rupp, “The Vienna LTE simulators—Enabling reproducibility in wireless communications research,” EURASIP Journal on Advances in Signal Processing, vol. 2011, art. 29, 2011. DOI: 10.1186/1687-6180-2011-29.

F. Capozzi, G. Piro, L. A. Grieco, G. Boggia, and P. Camarda, “Downlink packet scheduling in LTE cellular networks: Key design issues and a survey,” IEEE Communications Surveys & Tutorials, vol. 15, no. 2, pp. 678–700, 2013. DOI: 10.1109/SURV.2012.060912.00100.

S. Parkvall, A. Furuskär, and E. Dahlman, “Evolution of LTE toward IMT-Advanced,” IEEE Communications Magazine, vol. 49, no. 2, pp. 84–91, 2011. DOI: 10.1109/MCOM.2011.5706315.

Z. H. Mir and F. Filali, “LTE and IEEE 802.11p for vehicular networking: A performance evaluation,” EURASIP Journal on Wireless Communications and Networking, vol. 2014, art. 89, 2014. DOI: 10.1186/1687-1499-2014-89.

Y. Zhou and B. Ai, “Handover schemes and algorithms of high-speed mobile environment: A survey,” Computer Communications, vol. 47, pp. 1–15, 2014. DOI: 10.1016/j.comcom.2014.04.005.

Parichehreh, S. Savazzi, L. Goratti, and U. Spagnolini, “Seamless LTE connectivity in high-speed trains,” Wireless Communications and Mobile Computing, vol. 16, pp. 1478–1494, 2016. DOI: 10.1002/wcm.2607.

L. C. Gimenez, M. C. Cascino, M. Stefan, K. I. Pedersen, and A. F. Cattoni, “Mobility performance in slow- and high-speed LTE real scenarios,” in Proc. IEEE 83rd Vehicular Technology Conference (VTC Spring), 2016. DOI: 10.1109/VTCSpring.2016.7504347.