



Archives available at journals.mriindia.com

International Journal Of Advanced Chemical Science and Applications

ISSN: 2347-7601

Volume 5 Issue 01, 2016

Production and Characterization of Bioethanol from Agricultural Waste Materials

Saffiya Pavlidaki

Department of Computer Science and Engineering, Padma Institute of Business and Management, Bangladesh

saffiya.pavlidaki@pibm-bd.org

Peer Review Information

Submission: 28 Jan 2016

Revision: 12 Feb 2016

Acceptance: 07 March 2016

Keywords

Bioethanol, Agricultural waste, Lignocellulosic biomass, Enzymatic hydrolysis, *Saccharomyces cerevisiae*.

Abstract

Agricultural residues are abundant lignocellulosic resources that can be converted into second-generation bioethanol while reducing open burning and dependence on edible feedstocks. This methodology paper develops a comparative laboratory framework for production and characterization of bioethanol from rice straw, wheat straw, and sugarcane bagasse. The process consists of feedstock preparation, alkaline pretreatment, enzymatic hydrolysis, fermentation with *Saccharomyces cerevisiae*, ethanol recovery by fractional distillation, and physicochemical characterization. Pretreatment is designed to reduce lignin-associated recalcitrance and increase cellulose accessibility, whereas cellulase and beta-glucosidase convert exposed polysaccharides to fermentable sugars. Fermentation performance is evaluated from reducing-sugar utilization, ethanol concentration, yield, productivity, and theoretical fermentation efficiency. Recovered ethanol is characterized by alcohol strength, density, refractive index, Fourier-transform infrared spectroscopy and, where available, gas chromatography. An illustrative methodology-validation dataset is presented to demonstrate data handling; it indicates increasing hydrolysate sugar concentration and ethanol production in the order rice straw < wheat straw < sugarcane bagasse, with the bagasse system reaching 27.6 g/L ethanol and approximately 91.9% theoretical fermentation efficiency. These values are not reported as original experimental observations, but as worked examples showing how the proposed protocol can be analyzed. The integrated approach provides a reproducible basis for comparing agricultural wastes and identifying process bottlenecks related to delignification, enzymatic digestibility, fermentation inhibition, and ethanol recovery. The method is suitable for small-scale academic studies and can be extended to optimization studies involving pretreatment severity, enzyme loading, solids concentration, yeast dose, temperature and fermentation time.

Introduction

Bioethanol is a renewable oxygenated fuel that can partially substitute gasoline and can also serve as a platform solvent or chemical intermediate. Conventional ethanol production relies primarily on sugar- and starch-rich crops, but the food-versus-fuel concern and feedstock

cost have stimulated interest in lignocellulosic residues. Agricultural wastes such as rice straw, wheat straw, corn residues and sugarcane bagasse contain cellulose and hemicellulose that can be hydrolyzed to fermentable sugars; however, these polysaccharides are embedded in

a lignin-rich, structurally resistant matrix. Reviews published before 2016 consistently identify pretreatment, hydrolysis, fermentation and product recovery as the major technological stages governing second-generation ethanol productivity (Alvira et al., 2010; Achinas & Euverink, 2016; Chen & Fu, 2016).

Pretreatment is essential because lignin, cellulose crystallinity and limited pore accessibility restrict cellulase action. Alkaline processing is particularly attractive for agricultural residues because it can disrupt lignin-carbohydrate linkages, swell fibers and improve enzymatic accessibility with comparatively modest carbohydrate degradation. Rice-straw studies have demonstrated substantial improvement in enzymatic conversion after alkaline treatment, while sugarcane-bagasse and wheat-straw studies show that delignification and properly selected enzyme loading can markedly increase ethanol formation (Oberoi et al., 2012; Wanderley et al., 2013; Singhania et al., 2014). Simultaneous saccharification and fermentation can reduce end-product inhibition, but separate hydrolysis and fermentation remains methodologically useful when the objective is to characterize sugar release before fermentation and compare feedstock digestibility.

The present methodology therefore proposes a controlled comparative experiment using three common agricultural residues: rice straw, wheat straw and sugarcane bagasse. A common alkaline pretreatment and enzymatic hydrolysis protocol is applied to all feedstocks to permit direct comparison. *Saccharomyces cerevisiae* is selected as the fermenting organism because of its industrial relevance, ethanol tolerance and strong glucose-fermenting capacity. The study evaluates feedstock composition, sugar release, fermentation kinetics, ethanol yield and product characteristics. The principal objective is to establish a reproducible workflow for producing and characterizing bioethanol from agricultural wastes and to define the analytical calculations needed to compare conversion efficiency across feedstocks. The work is methodological in nature; any numerical results included below are

explicitly illustrative and should be replaced by measured laboratory data when the protocol is experimentally executed.

Literature Review

Alvira et al. (2010) reviewed pretreatment technologies and emphasized that the pretreatment step must improve cellulose accessibility while minimizing inhibitor formation and carbohydrate loss. Li et al. (2010) demonstrated that aqueous-ammonia-pretreated corn stover could be converted to ethanol through a two-phase simultaneous saccharification and fermentation strategy, highlighting the importance of preserving both glucan and xylan. Guragain et al. (2011) compared pretreatment methods for wheat straw and showed that pretreatment choice significantly affects downstream sugar recovery. Oberoi et al. (2012) reported efficient ethanol production from alkali-treated rice straw, obtaining high glucan conversion and demonstrating the value of alkaline delignification. Salehi et al. (2012) similarly reported effective rice-straw conversion after sodium-carbonate pretreatment. Wanderley et al. (2013) showed that combined pretreatment and fed-batch enzymatic hydrolysis improved ethanol production from sugarcane bagasse. For wheat straw, optimization of simultaneous saccharification and fermentation confirmed that temperature, enzyme loading, yeast concentration and pH interact strongly and should be controlled rather than varied independently (Zhang et al., 2013). Singhania et al. (2014) showed that efficient cellulase systems can improve wheat-straw conversion, while Saha et al. (2015) demonstrated pilot-scale conversion and confirmed that inhibitor management and high-solids operation become increasingly important during scale-up. By 2016, integrated reviews emphasized selective fractionation, enzyme synergy, robust fermenting organisms and process integration as the major routes toward industrial feasibility (Achinas & Euverink, 2016; Chen & Fu, 2016; Zabed et al., 2016).

Table 1. Selected literature informing the proposed methodology

Study	System	Methodological implication
Alvira et al., 2010	Pretreatment review	Pretreatment must increase enzyme accessibility while limiting inhibitors.
Oberoi et al., 2012	Rice straw; alkali + SSF	Alkaline delignification strongly improved glucan conversion.
Salehi et al., 2012	Rice straw; Na ₂ CO ₃	Alkaline carbonate pretreatment enabled efficient ethanol conversion.

Wanderley et al., 2013	Sugarcane bagasse	Combined pretreatment and fed-batch hydrolysis increased ethanol production.
Zhang et al., 2013	Wheat straw; RSM-SSF	Temperature, enzyme loading, yeast dose and pH significantly affect yield.
Singhania et al., 2014	Wheat straw	SSF outperformed SHF with an effective cellulase preparation.
Saha et al., 2015	Wheat straw; pilot scale	Scale-up requires inhibitor control and adequate solids handling.
Chen & Fu, 2016	Industrial review	Integrated fractionation, enzyme synergy and robust strains improve feasibility.

Methodology

1. Experimental design and feedstock selection

Three lignocellulosic agricultural wastes—rice straw, wheat straw and sugarcane bagasse—are evaluated under an identical conversion protocol. Each feedstock is analyzed in triplicate. Fresh residues are collected from clean agricultural or processing sources, manually sorted to remove soil and foreign matter, washed with tap water followed by distilled water, oven-dried at 60 ± 2 °C to constant mass, milled, and sieved to approximately 0.5–1.0 mm particle size. The dried powders are stored in airtight containers at room temperature. Moisture, ash, cellulose, hemicellulose and acid-insoluble lignin are determined using standard gravimetric/fiber-analysis procedures. The comparative design is intended to identify how intrinsic feedstock composition influences pretreatment efficiency, enzymatic sugar release and final ethanol formation.

2. Alkaline pretreatment

For each feedstock, 20 g dry biomass is mixed with 200 mL of 2% (w/v) NaOH, giving a 1:10 solid-to-liquid ratio. The suspension is heated at 121 °C for 30 min in an autoclave and allowed to cool. The solid fraction is recovered by filtration and repeatedly washed with distilled water until the wash liquid reaches approximately neutral pH. The treated material is dried at 60 °C to constant mass and weighed to determine solid recovery. This condition is selected as a practical common treatment for comparing agricultural residues; alkaline pretreatment is known to disrupt lignin structure and improve cellulose accessibility (Alvira et al., 2010; Oberoi et al., 2012). A second compositional analysis is performed on the dried pretreated solids to quantify cellulose enrichment and lignin removal.

3. Enzymatic hydrolysis

Pretreated solids are suspended at 10% (w/v) in 50 mM sodium-citrate buffer, pH 4.8. Commercial cellulase is added at 20 FPU per gram of dry

pretreated substrate and beta-glucosidase at 10 CBU/g substrate. Hydrolysis is conducted at 50 °C and 150 rpm for 48 h. Samples are withdrawn at 0, 12, 24, 36 and 48 h, centrifuged, and the supernatant is analyzed for reducing sugars by the DNS method or, when available, glucose and xylose by HPLC. Sugar release is expressed in g/L and also normalized to dry biomass. The hydrolysate is then adjusted to fermentation pH and heat-treated or membrane-filtered when aseptic operation is required.

4. Fermentation

Saccharomyces cerevisiae is propagated in yeast-peptone-dextrose medium for 18–24 h at 30 °C. Hydrolysates are adjusted to pH 5.0, supplemented with 1 g/L yeast extract and 0.5 g/L MgSO₄ where required, and inoculated to an initial yeast concentration of approximately 1×10^7 cells/mL. Fermentation is conducted in air-locked flasks at 30 °C and 100 rpm for 72 h. Samples collected at 0, 12, 24, 48 and 72 h are analyzed for residual reducing sugar and ethanol. This temperature favors *S. cerevisiae* activity and avoids the higher-temperature compromise inherent in simultaneous saccharification and fermentation. The decrease in sugar and increase in ethanol are used to determine productivity and fermentation efficiency.

5. Ethanol recovery and characterization

At the end of fermentation, biomass cells and suspended solids are removed by centrifugation. The clarified broth is subjected to fractional distillation, and the ethanol-rich fraction is collected near 78–85 °C. Ethanol concentration is quantified by gas chromatography with flame-ionization detection when available; alternatively, a calibrated alcohol hydrometer or dichromate method may be used. Recovered product is characterized by density at 20 °C, refractive index, and FTIR spectroscopy. A typical ethanol FTIR spectrum should show a broad O–H stretching band around 3200–3500 cm⁻¹, C–H stretching near 2970 cm⁻¹ and strong C–O stretching close to 1040–1100 cm⁻¹. GC

retention time and peak area are compared with analytical-grade ethanol.

6. Calculations and statistical analysis

Ethanol yield on consumed sugar is calculated as $YP/S = P/(S_0 - S_f)$, where P is ethanol produced (g/L), S_0 is initial fermentable sugar and S_f is residual sugar. The theoretical maximum conversion of glucose to ethanol is 0.511 g/g; therefore, fermentation efficiency (%) = $[YP/S / 0.511] \times 100$. Volumetric productivity is ethanol

concentration divided by fermentation time. Pretreatment solid recovery and lignin removal are calculated from dry-mass and compositional measurements before and after pretreatment. Triplicate data are reported as mean $\pm$ standard deviation. One-way ANOVA followed by Tukey's test ($p < 0.05$) is used to compare feedstocks. Correlation analysis may be used to relate cellulose enrichment, reducing-sugar release and ethanol yield.




Figure 1. Step-by-step methodology for conversion of agricultural waste to bioethanol.

Table 2. Core process conditions used in the methodology

Stage	Operating condition / measurement
Pretreatment	2% NaOH; 1:10 solid/liquid; 121 °C; 30 min
Hydrolysis	10% solids; pH 4.8; 20 FPU cellulase/g; 50 °C; 48 h
Fermentation	<i>S. cerevisiae</i> ; pH 5.0; 30 °C; 72 h
Recovery	Fractional distillation; ethanol-rich fraction near 78–85 °C
Characterization	Ethanol concentration, density, refractive index, FTIR, optional GC-FID

Results

Alkaline treatment increased the apparent cellulose fraction and decreased lignin content for all three feedstocks. The strongest cellulose enrichment in the illustrative dataset occurred in sugarcane bagasse, from 42.1% to 58.1%, while lignin decreased from 21.0% to 11.8%. Wheat straw showed a comparable improvement and

rice straw exhibited a slightly lower degree of delignification. Such changes are consistent with the role of alkali in disrupting ester bonds and lignin-carbohydrate associations, thereby exposing cellulose to hydrolytic enzymes. Previous rice-straw and wheat-straw studies similarly reported improved enzymatic conversion after alkaline pretreatment (Oberoi et al., 2012; Zhang et al., 2013).

Table 3. Illustrative feedstock composition and conversion results

Feedstock	Cellulose raw (%)	Cellulose after pretreat. (%)	Lignin raw (%)	Lignin after pretreat. (%)	Sugar after 48 h (g/L)	Ethanol 72 h (g/L)	Efficiency (%)
Rice straw	36.2	52.4	18.9	10.7	49.2	21.2	84.3
Wheat straw	38.5	55.3	17.2	9.5	53.6	23.9	87.3
Sugarcane bagasse	42.1	58.1	21.0	11.8	58.8	27.6	91.9

After 48 h hydrolysis, reducing-sugar concentrations were 49.2, 53.6 and 58.8 g/L for rice straw, wheat straw and sugarcane bagasse, respectively. The corresponding 72 h ethanol concentrations were 21.2, 23.9 and 27.6 g/L. This ranking indicates that greater cellulose enrichment and improved enzyme accessibility

translated into greater fermentable-sugar availability and ethanol production. Sugarcane bagasse showed the highest illustrative fermentation efficiency (91.9% of the glucose-to-ethanol theoretical value), followed by wheat straw (87.3%) and rice straw (84.3%). The proposed values are compatible with the broad

range reported in pre-2016 literature, where process configuration, pretreatment severity, enzyme loading, solids concentration and microbial strain substantially influenced ethanol concentration and yield (Li et al., 2010; Wanderley et al., 2013; Saha et al., 2015).




Figure 2. Illustrative reducing-sugar and ethanol concentrations for the three agricultural wastes.

Table 4. Illustrative characterization of recovered bioethanol

Feedstock	Alcohol strength (% v/v)	Density at 20 °C (g/mL)	Refractive index	Major FTIR bands (cm ⁻¹)	Interpretation
Rice straw	90.8	0.823	1.366	3335, 2973, 1048	Ethanol-rich fraction; residual water
Wheat straw	92.1	0.817	1.365	3332, 2971, 1047	Ethanol-rich fraction; low nonvolatile residue
Sugarcane bagasse	93.4	0.811	1.365	3329, 2970, 1046	Highest ethanol strength in comparison

For an experimental paper, the most informative statistical comparison would be a one-way ANOVA of ethanol yield among feedstocks, supported by triplicate measurements and a Tukey post-hoc test. A significant feedstock effect would then be interpreted together with compositional changes rather than from ethanol concentration alone. Higher cellulose after pretreatment, lower residual lignin and greater sugar release should be positively associated with ethanol productivity. If an optimization phase is added, response-surface methodology could be applied to enzyme loading, solids concentration, fermentation temperature and time. Such multivariable optimization has been effective for wheat-straw ethanol systems and can reduce the risk of selecting conditions from one-factor-at-a-time experiments (Zhang et al., 2013).

Conclusion and Discussion

This methodology provides a comparative route for producing and characterizing second-generation bioethanol from rice straw, wheat straw and sugarcane bagasse. The sequence of alkaline pretreatment, enzymatic hydrolysis, yeast fermentation and fractional distillation is

Ethanol characterization is used to verify that the recovered product is chemically consistent with ethanol rather than relying only on fermentation mass balance. In the illustrative dataset, the recovered fractions show alcohol strengths of approximately 90.8–93.4% (v/v). Density values remain slightly above that of anhydrous ethanol because residual water is retained after ordinary fractional distillation. Refractive indices are close across feedstocks, and FTIR bands are expected at the characteristic O–H, C–H and C–O regions. Where GC-FID is available, a dominant ethanol peak with minimal higher-alcohol or aldehyde peaks provides stronger confirmation of product quality. Product characterization is especially important when agricultural hydrolysates contain soluble inhibitors or fermentation by-products that may co-distill or interfere with colorimetric ethanol assays.

technically simple enough for an academic laboratory yet captures the main conversion barriers recognized in lignocellulosic ethanol research. The central methodological requirement is to treat all feedstocks under identical baseline conditions so that differences in sugar release and ethanol formation can be linked to biomass composition rather than inconsistent processing. The illustrative results suggest that sugarcane bagasse could provide the highest ethanol concentration under the proposed conditions because of favorable cellulose enrichment and hydrolysis performance, but this conclusion must be verified experimentally. Pretreatment severity should be optimized carefully: insufficient delignification limits enzyme accessibility, whereas excessive alkali, temperature or residence time can increase chemical consumption, carbohydrate loss and wastewater generation. Enzyme dosage is another major cost variable. Industrial reviews published through 2016 emphasize integrated fractionation, enzyme synergy, high-solids processing and inhibitor-tolerant microorganisms as the main directions for improving economic feasibility (Achinas & Euverink, 2016; Chen & Fu, 2016;

Zabed et al., 2016). Future work should therefore evaluate higher solids loading, enzyme recycling, fermentation of pentose-rich fractions, and energy-efficient ethanol recovery. With measured data replacing the illustrative values, the proposed protocol can support a concise research paper comparing agricultural wastes for sustainable bioethanol production.

References

- Alvira, P., Tomás-Pejó, E., Ballesteros, M., & Negro, M. J. (2010). Pretreatment technologies for an efficient bioethanol production process based on enzymatic hydrolysis: A review. *Bioresource Technology*, 101(13), 4851–4861. <https://doi.org/10.1016/j.biortech.2009.11.093>
- Li, X., Kim, T. H., & Nghiem, N. P. (2010). Bioethanol production from corn stover using aqueous ammonia pretreatment and two-phase simultaneous saccharification and fermentation (TPSSF). *Bioresource Technology*, 101(15), 5910–5916. <https://doi.org/10.1016/j.biortech.2010.03.015>
- Guragain, Y. N., De Coninck, J., Husson, F., Durand, A., & Rakshit, S. K. (2011). Comparison of some new pretreatment methods for second generation bioethanol production from wheat straw and water hyacinth. *Bioresource Technology*, 102(6), 4416–4424. <https://doi.org/10.1016/j.biortech.2010.11.125>
- Oberoi, H. S., Babbar, N., Sandhu, S. K., Dhaliwal, S. S., Kaur, U., Chadha, B. S., & Bhargava, V. K. (2012). Ethanol production from alkali-treated rice straw via simultaneous saccharification and fermentation using newly isolated thermotolerant *Pichia kudriavzevii* HOP-1. *Journal of Industrial Microbiology & Biotechnology*, 39(4), 557–566. <https://doi.org/10.1007/s10295-011-1060-2>
- Salehi, S. M. A., Karimi, K., Behzad, T., & Poornejad, N. (2012). Efficient conversion of rice straw to bioethanol using sodium carbonate pretreatment. *Energy & Fuels*, 26(12), 7354–7361. <https://doi.org/10.1021/ef301476b>
- Wanderley, M. C. A., Martín, C., Rocha, G. J. M., & Gouveia, E. R. (2013). Increase in ethanol production from sugarcane bagasse based on combined pretreatments and fed-batch enzymatic hydrolysis. *Bioresource Technology*, 128, 448–453. <https://doi.org/10.1016/j.biortech.2012.10.131>
- Zhang, W., Lin, Y., Zhang, Q., Wang, X., Wu, D., & Kong, H. (2013). Optimisation of simultaneous saccharification and fermentation of wheat straw for ethanol production. *Fuel*, 112, 331–337. <https://doi.org/10.1016/j.fuel.2013.05.064>
- Singhania, R. R., Saini, J. K., Saini, R., Adsul, M., Mathur, A., Gupta, R., & Tuli, D. K. (2014). Bioethanol production from wheat straw via enzymatic route employing *Penicillium janthinellum* cellulases. *Bioresource Technology*, 169, 490–495. <https://doi.org/10.1016/j.biortech.2014.07.011>
- Saha, B. C., Nichols, N. N., Qureshi, N., Kennedy, G. J., Iten, L. B., & Cotta, M. A. (2015). Pilot scale conversion of wheat straw to ethanol via simultaneous saccharification and fermentation. *Bioresource Technology*, 175, 17–22. <https://doi.org/10.1016/j.biortech.2014.10.060>
- Achinas, S., & Euverink, G. J. W. (2016). Consolidated briefing of biochemical ethanol production from lignocellulosic biomass. *Electronic Journal of Biotechnology*, 23, 44–53. <https://doi.org/10.1016/j.ejbt.2016.07.006>
- Chen, H., & Fu, X. (2016). Industrial technologies for bioethanol production from lignocellulosic biomass. *Renewable and Sustainable Energy Reviews*, 57, 468–478. <https://doi.org/10.1016/j.rser.2015.12.069>
- Zabed, H., Sahu, J. N., Suely, A., Boyce, A. N., & Faruq, G. (2016). Fuel ethanol production from lignocellulosic biomass: An overview on feedstocks and technological approaches. *Renewable and Sustainable Energy Reviews*, 66, 751–774. <https://doi.org/10.1016/j.rser.2016.08.038>