



Archives available at journals.mriindia.com

International Journal of Advanced Electrical and Electronics Engineering

ISSN: 2278-8948

Volume 10 Issue 01, 2021

Comparative Evaluation of Green Solvents for Sustainable Organic Synthesis Processes

Nimisha Braginskaya

Department of Electronics and Communication Engineering, Chiang Thon College of Management, Thailand
nimisha.braginskaya@ctcm-th.org

Peer Review Information

Submission: 12 Jan 2021

Revision: 09 March 2021

Acceptance: 10 April 2021

Keywords

Green Solvents, Sustainable Organic Synthesis, Solvent Selection, Deep Eutectic Solvents, Green Chemistry.

Abstract

Solvents frequently constitute the largest material fraction of an organic synthesis process and strongly influence worker safety, emissions, energy demand, waste generation, reaction rate and downstream separation. This methodology paper develops a comparative framework for selecting green solvents for sustainable organic synthesis. Six representative media—water, ethanol, 2-methyltetrahydrofuran (2-MeTHF), γ -valerolactone (GVL), glycerol and a choline-chloride-based deep eutectic solvent (DES)—are assessed through a combined experimental and multi-criteria protocol. The proposed workflow uses a standardized Knoevenagel condensation as a model transformation and evaluates reaction yield, reaction time, solvent recovery, energy requirement, safety-health-environment (SHE) profile, renewability and waste-related indicators. A weighted sustainability index is then applied to compare solvent performance without treating any single property as sufficient to define 'greenness'. Literature available through 2021 shows that water and bio-derived solvents can markedly reduce hazard and life-cycle burden, while emerging solvents such as GVL and DES can provide useful polarity and low volatility but may impose recovery or viscosity penalties. The methodology therefore emphasizes fit-for-purpose solvent selection rather than a universal ranking. Illustrative benchmark results demonstrate how the framework can identify balanced solvent choices for laboratory and process-scale organic synthesis while preserving transparency between measured data and sustainability scoring.

Introduction

Organic synthesis traditionally depends on volatile organic solvents for dissolution, heat transfer, reaction control, extraction, crystallization and cleaning. Because solvent mass can greatly exceed the mass of reagents and products, solvent choice is a major determinant of the environmental footprint of fine-chemical and pharmaceutical manufacture. Sheldon [1] highlighted alternative reaction media as a central element of sustainable synthesis, while Capello et al. [2] demonstrated that a solvent

cannot be called green from one property alone: hazard, emissions, resource demand and life-cycle effects should be considered together. Industrial guides subsequently translated these concepts into practical solvent-selection tools [5,8,9].

The challenge is that solvent substitution often creates trade-offs. Water is non-flammable and inexpensive, but poor substrate solubility and energy-intensive evaporation may limit some processes. Ethanol is renewable and versatile, but it remains flammable. 2-MeTHF is useful for

biphasic work-up and can originate from renewable feedstocks [4], whereas high-boiling solvents such as GVL may reduce volatile emissions but increase separation energy unless recycling is efficient [11]. Glycerol can be a low-toxicity bio-derived reaction medium [7], while ionic liquids and DES offer negligible vapor pressure and tunable properties, although their full life-cycle profile depends strongly on composition and recovery [3,10,16].

Accordingly, this paper proposes a step-by-step methodology to compare solvents under identical synthetic conditions and to combine reaction performance with SHE and process metrics. The objective is not to declare a universally 'best' solvent, but to identify the most balanced option for a defined organic transformation and to provide a reproducible decision framework compatible with CHEM21-style thinking [13,14] and broader sustainable-solvent assessments [12,15].

Literature Review

Sheldon [1] reviewed water, supercritical fluids, ionic liquids and other alternative media and established solvent replacement as a key pathway toward more sustainable organic synthesis. Capello et al. [2] advanced this discussion by integrating substance hazards with emissions and resource use over the solvent life cycle, showing why low toxicity or low volatility alone is insufficient.

Plechko and Seddon [3] documented industrial applications of ionic liquids and emphasized the opportunities created by tunable physicochemical properties. Aycock [4] described 2-MeTHF as a renewable-resource-derived solvent with useful properties for organometallic and biphasic chemistry. Henderson et al. [5] expanded the GSK solvent

selection guide to 110 solvents and separated reactivity, fire/explosion, health and environmental considerations, making solvent assessment more practical for medicinal chemistry.

Jessop [6] argued that the search for green solvents must remain application-specific because each solvent combines benefits and disadvantages. Díaz-Álvarez et al. [7] reviewed glycerol and glycerol-derived media for synthetic chemistry, demonstrating that a biodiesel by-product can serve as a useful low-volatility reaction medium. Jiménez-González et al. [8] identified solvent and process improvement as priority areas for sustainable pharmaceutical and fine-chemical manufacturing.

Prat et al. [9] presented the Sanofi solvent selection guide, reinforcing the need for early-stage solvent screening before process choices become difficult to change. Smith et al. [10] established DES as a distinct class of ionic-liquid analogues with tunable properties and simple preparation. Ismalaj et al. [11] demonstrated GVL as a renewable dipolar aprotic medium for Hiyama coupling, illustrating the synthetic utility of biomass-derived solvents.

Welton [12] emphasized that sustainable solvent choice should consider the complete chemical process, not merely solvent toxicity. Prat et al. [13] and Byrne et al. [14] consolidated solvent-selection tools and provided comparative SHE-oriented guidance for classical and less-classical solvents. Clarke et al. [15] reviewed the rapidly expanding portfolio of sustainable solvents and highlighted the importance of techno-economic and life-cycle context. Hansen et al. [16] provided a 2021 critical review of DES fundamentals, including the need for better property prediction and more rigorous understanding of composition–property relationships.

Table 1. Key literature informing the comparative solvent-selection methodology.

Reference	Solvent / framework	Main contribution	Methodological implication
Capello et al. [2]	Life-cycle solvent assessment	Hazard + emissions + resource use	Use multiple dimensions, not one label
Henderson et al. [5]	GSK guide	Industrial SHE ranking	Screen safety, health and environment separately
Prat et al. [13]	CHEM21 guide	Classical and emerging solvent ranking	Use standardized decision criteria
Clarke et al. [15]	Sustainable solvent review	Alternative solvent families and trade-offs	Include recovery and process context
Hansen et al. [16]	Deep eutectic solvents	DES fundamentals and limitations	Treat viscosity, purity and recycling explicitly

Methodology

1. Study Design and Candidate Solvents

The study is designed as a controlled solvent-screening experiment combined with a multi-criteria sustainability assessment. Six candidate media are selected to represent distinct green-solvent strategies: water (benign aqueous medium), ethanol (renewable protic solvent), 2-MeTHF (renewable ether), GVL (biomass-derived dipolar aprotic solvent), glycerol (bio-derived polyol) and choline chloride/urea DES (low-volatility eutectic medium). Selection follows the principle that solvents should cover different polarity, volatility, recovery and hazard profiles.

2. Standardized Model Reaction

A Knoevenagel condensation between benzaldehyde (1.0 mmol) and malononitrile (1.0 mmol) is proposed as the model organic transformation. Piperidine (5 mol%) is used as the catalyst. Each reaction is performed using 5 mL of the test solvent at 50 °C with vigorous stirring. Samples are withdrawn at fixed intervals and analyzed by gas chromatography (GC) or HPLC. The reaction is stopped after 60 min or after conversion exceeds 95%. Product is isolated by crystallization, filtration or liquid-liquid work-up depending on solvent behavior. Each condition should be run in triplicate, and mean $\pm$ standard deviation reported. The same reagent batch, vessel geometry, agitation rate and analytical method are maintained for all solvents.

3. Step-by-Step Experimental Procedure

1. Dry or condition each solvent to a defined water content and record density, boiling point and recovery method.
2. Charge benzaldehyde and malononitrile into a 25 mL reaction vial; add 5 mL of the selected solvent and piperidine catalyst.
3. Stir the sealed reaction at 50 °C. Record temperature, stirring speed and time to ensure identical thermal history.
4. Withdraw aliquots at 10, 20, 30, 45 and 60 min; quantify substrate conversion and product formation by calibrated GC/HPLC.
5. Isolate the product and determine isolated yield, purity and any additional solvent required for extraction or washing.
6. Recover the reaction solvent by distillation, phase separation or vacuum treatment as appropriate; calculate recovery percentage.
7. Repeat the reaction at least three times and perform one solvent-reuse cycle to test robustness.
8. Calculate green metrics and the weighted sustainability index; rank solvents only after both reaction and sustainability data are available.



Figure 1. Step-by-step framework for comparative evaluation of green solvents in organic synthesis.

4. Green Metrics and Multi-Criteria Scoring

For each solvent, the analysis records: (i) isolated yield; (ii) reaction time; (iii) solvent recovery; (iv) process mass intensity (PMI); (v) E-factor; (vi) estimated energy needed for heating and solvent removal; and (vii) SHE-related scores. The sustainability index is normalized on a 1–5 scale using six criteria: safety (20%), human health (20%), environmental profile (20%), renewability (15%), recoverability (10%) and

synthetic versatility (15%). The weighted index is calculated as:

$$SI = 0.20S + 0.20H + 0.20E + 0.15R + 0.10Rec + 0.15V$$

where S, H, E, R, Rec and V denote normalized scores for safety, health, environment, renewability, recovery and versatility. The weights may be altered in a sensitivity analysis to reflect industrial priorities. This avoids presenting the final rank as an absolute property of the solvent.

Table 2. Main variables and measurements in the proposed comparative study.

Variable	Controlled / measured value	Purpose	Analysis
Reaction temperature	50 °C	Equal thermal input	Thermocouple
Solvent volume	5 mL	Equal solvent intensity	Volumetric measurement
Reaction time	0-60 min	Kinetic comparison	GC/HPLC sampling

Product yield	Measured (%)	Synthetic efficiency	Isolated mass + assay
Solvent recovery	Measured (%)	Circularity / cost	Mass balance
SHE / renewability	1-5 normalized score	Sustainability	Published guides + SDS

Results

Important methodological note: the values in Tables 3–4 and Figure 2 are an illustrative benchmark dataset used to demonstrate the proposed analysis. They are not claimed as measurements from a completed experiment and should be replaced by laboratory data when the protocol is executed.

Comparative Sustainability Assessment

Application of the weighted scoring framework gives the highest illustrative index to water, followed closely by glycerol and GVL. The differences are intentionally modest because no solvent dominates every criterion. Water benefits from very low toxicity, non-flammability and low acquisition cost, but recovery by evaporation can

be energy intensive. Glycerol has favorable toxicity and renewable-feedstock characteristics, although high viscosity and boiling point can complicate separation. GVL combines high polarity, renewable origin and low volatility, but its relatively high boiling point makes efficient recycle important. Ethanol provides a strong balance of renewable sourcing, synthetic versatility and easy recovery, with flammability as its main limitation. 2-MeTHF provides excellent phase behavior and solvent recovery but requires fire-control measures. DES minimizes volatile emissions and offers tunability, but viscosity, water sensitivity and end-of-life data remain relevant concerns.

Table 3. Illustrative normalized multi-criteria scores used to demonstrate the ranking method.

Solvent	Safety	Health	Environment	Renewable	Recovery	Versatility	SI /5
Water	5.0	5.0	5.0	5.0	3.0	3.0	4.45
Glycerol	5.0	5.0	5.0	5.0	1.5	3.5	4.35
GVL	4.0	4.5	4.5	5.0	2.5	4.5	4.30
Ethanol	4.0	4.0	4.0	5.0	4.0	4.0	4.15
DES	4.5	4.5	4.5	4.0	2.0	4.0	4.05
2-MeTHF	3.5	4.0	4.0	4.5	4.5	4.5	4.05




Figure 2. Illustrative weighted sustainability index for the six candidate solvents.

1. Illustrative Process-Performance Benchmark

A second comparison combines expected laboratory observables with solvent recovery. The purpose is to demonstrate that a high sustainability score should not automatically override reaction performance. A solvent giving

excellent conversion but requiring large volumes for extraction, difficult drying, or energy-intensive recovery may be inferior at process scale. Conversely, a solvent with slightly lower intrinsic greenness may be preferable if it enables high selectivity, low solvent volume and near-complete recycle.

Table 4. Illustrative process-performance dataset for demonstrating the proposed analysis.

Solvent	Illustrative yield (%)	Time (min)	Recovery (%)	Main advantage	Main limitation
Water	88	60	85	Benign, non-flammable	Solubility / evaporation energy

Ethanol	93	45	90	Renewable and versatile	Flammable VOC
2-MeTHF	91	50	92	Easy phase separation	Flammability
GVL	94	40	88	Renewable polar aprotic medium	High boiling point
Glycerol	90	55	80	Low toxicity, bio-derived	Viscosity / recovery
DES	95	35	90	Low volatility, tunable	Viscosity / composition sensitivity

Interpretation

The comparative result supports three methodological conclusions. First, green solvent selection is a multi-objective optimization problem rather than a substitution based only on toxicity or renewability. Second, solvent recovery should be measured experimentally because it can reverse an apparent ranking when high-boiling or viscous media are used. Third, sensitivity analysis is necessary: pharmaceutical production may assign greater weight to worker safety and regulatory acceptance, whereas commodity processes may prioritize recovery energy and solvent cost. These conclusions are consistent with the logic of industrial solvent guides and sustainable-solvent reviews.

2. Sensitivity and Uncertainty Analysis

Because the weighting factors in the sustainability index reflect decision priorities, the ranking should be tested against alternative weight sets. A recommended sensitivity analysis increases one criterion at a time from its baseline weight to 30% while proportionally reducing the others. If the preferred solvent remains within the top two positions across most scenarios, the decision can be considered robust. If ranking changes substantially, the study should report a shortlist rather than a single winner. Experimental uncertainty in yield, recovery and energy measurements should also be propagated through the final process score using replicate standard deviations or simple Monte Carlo sampling. This is particularly important when candidate solvents differ by only a few tenths of a normalized score.

3. Industrial and Scale-Up Considerations

Scale-up can alter the apparent advantage of a solvent. Low-boiling media may be easy to distil but require closed equipment and vapor control; high-boiling media may reduce fugitive emissions but increase heating and drying duty. Water-rich systems may simplify safety management while increasing wastewater treatment. Bio-derived solvents can improve renewable-content metrics, yet availability,

purity, transport distance and solvent manufacture remain part of the life-cycle burden. For industrial deployment, the laboratory ranking should therefore be combined with solvent price, corrosion compatibility, regulatory status, recycle-loop design, product crystallization behavior and waste-treatment route.

A practical decision rule is to reject any solvent with an unacceptable safety or regulatory issue first, then compare the remaining candidates by reaction productivity and solvent recovery, and finally use the weighted sustainability index to resolve close alternatives. This staged strategy mirrors the logic of published industrial solvent guides and prevents a high aggregate score from masking a critical process hazard. The outcome of the proposed methodology is therefore a documented solvent-selection rationale that can be audited and updated when new toxicity, life-cycle or process-performance data become available.

Conclusion and Discussion

This paper presents a reproducible methodology for comparing green solvents in sustainable organic synthesis by combining controlled reaction screening with multi-criteria sustainability assessment. The proposed design compares water, ethanol, 2-MeTHF, GVL, glycerol and a choline-chloride-based DES using the same model reaction, analytical method and process boundaries. The approach integrates synthetic performance with safety, health, environmental impact, renewability, solvent recovery and versatility, thereby avoiding the common error of treating a single favorable property as proof of solvent greenness. Literature through 2021 demonstrates that water and renewable solvents can offer important benefits, but that practical performance, recovery and life-cycle context remain decisive [1,2,12,15].

The illustrative comparison suggests that water, glycerol and GVL may score strongly on broad sustainability criteria, whereas ethanol and 2-MeTHF can be especially attractive when easy recovery and operational flexibility are

important. DES can provide very low volatility and tunable reaction environments, but viscosity, water content, component toxicity and recycling must be characterized rather than assumed [10,16]. For real experimental use, the benchmark values reported here should be replaced with triplicate measured data, and the solvent ranking should be recalculated with uncertainty ranges and sensitivity analysis. Future work should extend the framework to several reaction classes, continuous-flow processing, solvent blends, life-cycle assessment and economic costing. Such integration would make solvent selection a quantitative design decision rather than a qualitative label.

References

- Sheldon, R. A. (2005). Green solvents for sustainable organic synthesis: state of the art. *Green Chemistry*, 7, 267-278. DOI: 10.1039/B418069K.
- Capello, C., Fischer, U., & Hungerbühler, K. (2007). What is a green solvent? A comprehensive framework for the environmental assessment of solvents. *Green Chemistry*, 9, 927-934. DOI: 10.1039/B617536H.
- Plechkova, N. V., & Seddon, K. R. (2008). Applications of ionic liquids in the chemical industry. *Chemical Society Reviews*, 37, 123-150. DOI: 10.1039/B006677J.
- Aycock, D. F. (2007). Solvent applications of 2-methyltetrahydrofuran in organometallic and biphasic reactions. *Organic Process Research & Development*, 11, 156-159. DOI: 10.1021/op060155c.
- Henderson, R. K., Jiménez-González, C., Constable, D. J. C., et al. (2011). Expanding GSK's solvent selection guide - embedding sustainability into solvent selection starting at medicinal chemistry. *Green Chemistry*, 13, 854-862. DOI: 10.1039/C0GC00918K.
- Jessop, P. G. (2011). Searching for green solvents. *Green Chemistry*, 13, 1391-1398. DOI: 10.1039/C0GC00797H.
- Díaz-Álvarez, A. E., Francos, J., Lastra-Barreira, B., Crochet, P., & Cadierno, V. (2011). Glycerol and derived solvents: new sustainable reaction media for organic synthesis. *Chemical Communications*, 47, 6208-6227. DOI: 10.1039/C1CC10620A.
- Jiménez-González, C., Poehlauer, P., Broxterman, Q. B., et al. (2011). Key green engineering research areas for sustainable manufacturing: a perspective from pharmaceutical and fine chemicals manufacturers. *Organic Process Research & Development*, 15, 900-911. DOI: 10.1021/op100327d.
- Prat, D., Pardigon, O., Flemming, H.-W., et al. (2013). Sanofi's solvent selection guide: a step toward more sustainable processes. *Organic Process Research & Development*, 17, 1517-1525. DOI: 10.1021/op4002565.
- Smith, E. L., Abbott, A. P., & Ryder, K. S. (2014). Deep eutectic solvents (DESs) and their applications. *Chemical Reviews*, 114, 11060-11082. DOI: 10.1021/cr300162p.
- Ismalaj, E., Strappaveccia, G., Ballerini, E., Elisei, F., Piermatti, O., Gelman, D., & Vaccaro, L. (2014). γ -Valerolactone as a renewable dipolar aprotic solvent deriving from biomass degradation for the Hiyama reaction. *ACS Sustainable Chemistry & Engineering*, 2, 2461-2464. DOI: 10.1021/sc5004727.
- Welton, T. (2015). Solvents and sustainable chemistry. *Proceedings of the Royal Society A*, 471, 20150502. DOI: 10.1098/rspa.2015.0502.
- Prat, D., Wells, A., Hayler, J., et al. (2016). CHEM21 selection guide of classical- and less classical-solvents. *Green Chemistry*, 18, 288-296. DOI: 10.1039/C5GC01008J.
- Byrne, F. P., Jin, S., Paggiola, G., et al. (2016). Tools and techniques for solvent selection: green solvent selection guides. *Sustainable Chemical Processes*, 4, 7. DOI: 10.1186/s40508-016-0051-z.
- Clarke, C. J., Tu, W.-C., Levers, O., Bröhl, A., & Hallett, J. P. (2018). Green and sustainable solvents in chemical processes. *Chemical Reviews*, 118, 747-800. DOI: 10.1021/acs.chemrev.7b00571.
- Hansen, B. B., Spittle, S., Chen, B., et al. (2021). Deep eutectic solvents: a review of fundamentals and applications. *Chemical Reviews*, 121, 1232-1285. DOI: 10.1021/acs.chemrev.0c00385.