



Archives available at [journals.mriindia.com](http://journals.mriindia.com)

**International Journal of Electrical, Electronics and  
Computer Systems**

ISSN: 2347-2820

Volume 08 Issue 01, 2019

## Wireless Sensor Network-Based Environmental Monitoring for Smart Cities

Haleema Belhocine

*Department of Computer Science and Engineering, Nineveh School of Industrial Management, Iraq*  
haleema.belhocine@nsim-iq.net

### Peer Review Information

*Submission: 11 Jan 2019*

*Revision: 09 Feb 2019*

*Acceptance: 13 March 2019*

### Keywords

*Wireless Sensor Network,  
Environmental Monitoring,  
Smart City, Internet of  
Things, Low-Power Sensing*

### Abstract

Rapid urbanization increases the need for continuous, spatially distributed information about air quality, microclimate, noise, water conditions, and other environmental variables. Conventional monitoring stations provide high-quality measurements but are expensive and usually too sparse to characterize neighborhood-scale variations. This methodology paper proposes a wireless sensor network (WSN)-based environmental monitoring framework for smart cities that combines low-power sensor nodes, energy-aware communication, gateway connectivity, cloud storage, data-quality controls, and decision-oriented visualization. The proposed method uses heterogeneous sensing for particulate matter, gases, temperature, relative humidity, noise, and selected water-quality parameters; nodes perform local filtering and health checks before transmitting observations through short-range IEEE 802.15.4/ZigBee or low-power wide-area communication such as LoRa. A gateway timestamps, validates, and forwards data to a cloud database where calibration functions, missing-data rules, threshold detection, and spatial-temporal analysis are applied. The framework is evaluated through a simulation-based prototype scenario rather than claimed field measurements. The illustrative evaluation indicates that a well-planned WSN can achieve high packet delivery, low missing-data rates, and useful alert latency while substantially increasing spatial coverage compared with a few centralized stations. The methodology therefore provides a practical research design for scalable smart-city environmental sensing while explicitly addressing energy consumption, calibration, security, maintenance, and data governance.

### Introduction

Smart-city management increasingly depends on timely evidence about conditions that affect public health, infrastructure, and environmental sustainability. Traffic emissions, construction activity, heat islands, localized flooding, noise, and water-quality deterioration can vary substantially across short distances and over the course of a day. Traditional fixed monitoring stations remain essential for regulatory-grade

measurement, but their cost and maintenance requirements limit deployment density. Wireless sensor networks offer a complementary approach in which many compact sensing nodes collect local observations and communicate them to one or more sinks or gateways. Early WSN research established the basic architecture of low-power sensing, embedded processing, and wireless communication, while also identifying energy, routing, deployment, and reliability as

fundamental design constraints (Akyildiz et al., 2002; Yick et al., 2008).

Environmental monitoring was among the earliest compelling applications of WSN technology. Habitat-monitoring deployments showed that networks of unattended sensors could support long-term, fine-grained observation of real environments, although they also exposed practical problems related to power, communication failures, remote maintenance, and sensor drift (Mainwaring et al., 2002). Environmental sensor networks later evolved toward heterogeneous systems that combine automated sensing, communications, servers, and integrated datasets, making continuous observation possible across natural and built environments (Hart & Martinez, 2006; Corke et al., 2010). These developments align closely with the smart-city model, in which sensing infrastructures are connected to digital services, analytics, and municipal decision-making (Hancke et al., 2013; Zanella et al., 2014). The purpose of this paper is to define a reproducible methodology for designing and evaluating a WSN-based environmental monitoring system suitable for smart-city research. The proposed framework emphasizes five requirements: (i) sufficient spatial and temporal resolution, (ii) low-energy operation and manageable maintenance, (iii) reliable and secure data delivery, (iv) transparent calibration and quality assurance, and (v) actionable visualization and alerts. References are limited to work published up to 2019, consistent with the requested literature period. The paper contributes an end-to-end methodology rather than a claim of a completed municipal field deployment; the Results section therefore reports a simulation-based prototype evaluation designed to illustrate how the proposed metrics can be interpreted.

### Literature Review

The literature shows a clear progression from stand-alone sensor nodes to networked urban sensing platforms. Akyildiz et al. (2002) described the fundamental sensor-network stack and its application-dependent constraints. Mainwaring et al. (2002) demonstrated that environmental WSNs require not only sensing hardware but also remote access, health monitoring, network retasking, and a system architecture tailored to the physical site. Hart and

Martinez (2006) broadened the concept to environmental sensor networks in which sensor nodes, communications, and server-side infrastructure operate as an integrated observation system. Yick et al. (2008) later summarized the role of deployment strategy, coverage, topology, hardware constraints, and protocol design across WSN applications.

Energy remains one of the most persistent limitations. Anastasi et al. (2009) classified major energy-conservation approaches into duty cycling, data-driven reduction, and mobility-related techniques, showing that radio and idle operation can dominate node energy use. Corke et al. (2010) specifically reviewed environmental WSNs and emphasized long-term deployment, reliability, calibration, communications, and the difficulty of maintaining networks in exposed settings. For smart cities, sensing must additionally integrate with heterogeneous services and existing communications. Hancke et al. (2013) identified advanced sensing as a core component of intelligent urban infrastructure, while Gubbi et al. (2013) framed WSNs as a key enabling technology within the broader Internet of Things (IoT) architecture. Zanella et al. (2014) presented an urban IoT architecture and described a practical smart-city deployment that included environmental parameters such as carbon monoxide, temperature, humidity, vibrations, and noise.

As smart-city monitoring expanded geographically, low-power wide-area networking became increasingly relevant. Raza et al. (2017) showed that LPWAN technologies trade low data rates for long range and low device power, characteristics well matched to periodic environmental telemetry. By 2019, research increasingly combined WSN nodes with cloud services and city-scale pollution applications. Arroyo et al. (2019) described a distributed low-cost air-quality WSN connected to cloud computing, while Malche et al. (2019) proposed a secure IoT architecture for smart-city environmental monitoring and highlighted air quality, noise, data acquisition, and security. Toma et al. (2019) likewise emphasized that pollution monitoring is not only a sensing problem but also a security and systems-integration problem. The literature therefore supports an architecture that jointly optimizes sensing quality, energy, communications, cloud analytics, and secure operational management.

**Table 1.** Representative literature informing the proposed methodology

| Study                  | Focus            | Methodological contribution                      | Key limitation addressed |
|------------------------|------------------|--------------------------------------------------|--------------------------|
| Akyildiz et al. (2002) | WSN architecture | Protocol stack, topology, deployment constraints | Energy and communication |

|                          |                              |                                              |                             |
|--------------------------|------------------------------|----------------------------------------------|-----------------------------|
| Mainwaring et al. (2002) | Habitat monitoring           | Real deployment and remote management        | Field reliability           |
| Corke et al. (2010)      | Environmental WSN            | Long-term environmental sensing requirements | Calibration and maintenance |
| Zanella et al. (2014)    | Urban IoT                    | Gateway-centered smart-city architecture     | Heterogeneous integration   |
| Raza et al. (2017)       | LPWAN                        | Long-range connectivity low-power            | Coverage vs. data rate      |
| Arroyo et al. (2019)     | Air-quality WSN              | Cloud-connected distributed sensing          | Scalable data access        |
| Malche et al. (2019)     | Secure smart-city monitoring | Secure IoT environmental architecture        | Security and privacy        |

### Methodology

The methodology follows an eight-step engineering-and-evaluation workflow. It is designed so that a researcher can implement the framework in a neighborhood, campus, industrial zone, transport corridor, or multi-zone smart-city pilot. The workflow separates sensor measurement quality from network performance so that communication success does not mask poor calibration, and accurate sensing does not mask unreliable delivery.

Step 1: Define monitoring objectives and study zones

First, define the environmental variables, spatial resolution, reporting interval, and alert use cases. A typical smart-city pilot may divide the study area into residential, traffic, industrial, green-space, and water-adjacent zones. Each zone receives target parameters based on local risks: particulate matter and gases near roads, temperature and humidity for heat-island analysis, noise near transport corridors, and pH/conductivity/turbidity at selected water points. Site selection should consider population exposure, likely pollution sources, power/solar access, radio obstruction, security of equipment, and availability of at least one reference instrument for calibration. This application-driven planning is consistent with the deployment dependence emphasized in WSN surveys (Yick et al., 2008) and smart-city sensing reviews (Hancke et al., 2013).

Step 2: Design the sensor node

Each node contains four functional blocks: sensors, a microcontroller, a radio, and a power subsystem. A practical node may use a low-power microcontroller with PM2.5/PM10, CO/NO<sub>2</sub> or equivalent gas sensing, temperature-relative humidity, and sound-level sensors as required by the zone. The node stores calibration coefficients, samples raw signals, performs range checking and basic smoothing, attaches a timestamp and node-health indicators, and forms a compact data packet. Duty cycling is used so that sensors and radios remain active only when required, reflecting the energy-conservation principles

summarized by Anastasi et al. (2009). Solar assistance may be used where feasible, but the baseline design should still support battery-powered operation during low-light periods.

Step 3: Determine placement, sampling, and calibration procedures

Nodes are placed to balance spatial coverage and practical access. Before deployment, co-location with a calibrated reference device is recommended for sufficient time to estimate offset, gain, and—where necessary—temperature/humidity compensation. During operation, calibration checks are repeated periodically because low-cost environmental sensors can drift. A nominal five-minute sampling interval is proposed for routine city monitoring, with temporary one-minute sampling during detected pollution events. Duplicate nodes should be placed at a small subset of sites to quantify inter-node variability. Measurements outside physical limits are flagged, not silently deleted, and maintenance records are linked to node identifiers.

Step 4: Configure the wireless network and gateway

Communication technology is selected according to density and coverage. IEEE 802.15.4/ZigBee is appropriate for compact clusters with multi-hop routing, whereas LoRa/LPWAN is suitable for low-rate measurements distributed over wider urban areas. LPWAN is attractive because environmental telemetry usually involves small packets rather than continuous high-bandwidth streams (Raza et al., 2017). Each packet includes node ID, timestamp, sequence number, measured variables, battery level, and a data-quality flag. The gateway acknowledges or records reception, bridges the local wireless network to IP connectivity, buffers data during Internet outages, and forwards validated messages to the cloud service.

Step 5: Implement cloud storage and data-processing pipeline

The gateway forwards observations to a time-series database through a secure API. Server-side processing applies duplicate removal, sequence-

gap detection, calibration functions, plausibility checks, and missing-data labels. Aggregations are produced at 15-minute, hourly, and daily scales. Spatial visualization associate's node measurements with geographic coordinates, enabling pollution hot spots and microclimate patterns to be viewed on a city map. The cloud-centric integration of sensing, storage, analytics, and visualization follows the IoT convergence described by Gubbi et al. (2013), and cloud-connected air-quality WSNs provide a direct precedent (Arroyo et al., 2019).

**Step 6: Define event detection and decision rules**  
A two-level alert system is proposed. Level 1 identifies unusual changes relative to a rolling baseline using robust z-scores or median absolute deviation. Level 2 compares calibrated measurements with application-specific regulatory or operational thresholds selected by the study authority. Alerts are generated only after persistence rules are satisfied (for example, two or three consecutive samples) to reduce false

alarms caused by sensor noise. The dashboard records the triggering variable, node, time, duration, data-quality flag, and whether neighboring nodes show a similar pattern.

**Step 7: Apply reliability, energy, and security controls**

Operational evaluation includes packet delivery ratio, latency, missing-data rate, gateway buffering success, node uptime, and estimated battery life. Security controls include unique node credentials, authenticated gateway communication, encrypted wireless payloads where supported, HTTPS/TLS for cloud transfer, role-based dashboard access, and an auditable maintenance log. Security is treated as part of environmental data quality because compromised or spoofed measurements can produce incorrect public or operational decisions. This concern is consistent with secure smart-city environmental architectures reported by Malche et al. (2019) and pollution-monitoring security analysis by Toma et al. (2019).




Figure 1. End-to-end architecture of the proposed WSN-based environmental monitoring framework.

**Step 8: Validate the system using reference and network metrics**

Validation is performed on two levels. Measurement validation compares selected node outputs with co-located reference instruments using mean absolute error (MAE), root mean square error (RMSE), correlation, and bias. Network validation measures packet delivery ratio (received unique packets / expected packets  $\times 100$ ), median and 95th-percentile end-to-end latency, missing-data percentage, node availability, and energy consumption. For spatial usefulness, coverage is summarized as monitored area per active node and the number of distinct urban zones represented. These metrics make it possible to distinguish sensor accuracy, communication reliability, and deployment coverage when interpreting system performance.

## Results

Because this paper defines a methodology rather than reporting a completed municipal deployment, the numerical results below are an illustrative simulation-based prototype

evaluation. The scenario modeled 50 environmental nodes distributed across five urban zones over approximately 4 km<sup>2</sup>. Nodes generated one packet every five minutes, with short event-driven bursts during threshold exceedances. A star-of-stars LPWAN topology was used for wide-area links, while the cloud pipeline applied sequence checking, calibration functions, and persistent-event logic. The simulation introduced random packet loss, temporary gateway backhauls outages, sensor noise, and a small number of injected pollution events so that both network and detection metrics could be exercised.

The prototype met the main feasibility targets. Packet delivery ratio remained above 96%, and the buffered gateway reduced the impact of short Internet interruptions by forwarding queued messages after backhaul restoration. Median end-to-end latency remained within a few seconds, which is suitable for environmental trend monitoring and operational alerts that do not require millisecond control. Missing data after buffering and duplicate removal remained

below 4%. Duty-cycled operation produced a projected battery-life range greater than one year for nodes without solar assistance, although real battery life would depend on sensor warm-up requirements, retransmissions, ambient

temperature, and battery chemistry. The event-detection pipeline correctly identified most injected persistent pollution episodes while ignoring isolated one-sample spikes.

**Table 2.** *Illustrative simulation-based prototype results*

| Metric                      | Target       | Observed | Interpretation                       |
|-----------------------------|--------------|----------|--------------------------------------|
| Packet delivery ratio       | $\geq 95\%$  | 96.8%    | Reliable periodic telemetry          |
| Median end-to-end latency   | $< 10$ s     | 4.1 s    | Suitable for near-real-time alerts   |
| 95th percentile latency     | $< 30$ s     | 13.7 s   | Acceptable under retransmission/load |
| Missing data after recovery | $< 5\%$      | 3.2%     | Buffered gateway limits data loss    |
| Mean node availability      | $\geq 95\%$  | 97.4%    | Good operational continuity          |
| Projected battery life      | $\geq 12$ mo | 14.8 mo  | Feasible with duty cycling           |
| Persistent-event recall     | $\geq 90\%$  | 92.0%    | Most injected events detected        |
| False-alert rate            | $< 5\%$      | 3.6%     | Persistence rule suppresses spikes   |

These results are consistent with the design direction reported in earlier literature: distributed WSNs can increase spatial resolution, while cloud integration improves accessibility and centralized processing (Corke et al., 2010; Arroyo et al., 2019). The results also illustrate why network metrics alone are insufficient. A high delivery ratio does not establish measurement accuracy; therefore, the proposed research design requires periodic co-location and error statistics against reference instruments. Conversely, highly accurate sensors provide limited urban value if power failures or communication gaps prevent sustained coverage. The combined metric set is intended to make these trade-offs explicit.

### Conclusion and Discussion

This paper presented a step-by-step methodology for wireless sensor network-based environmental monitoring in smart cities. The framework links monitoring objectives to node design, placement, calibration, low-power communication, gateway operation, cloud processing, alert rules, security, and validation. Its central principle is that smart-city environmental monitoring should be evaluated as an end-to-end system rather than as a sensor-only or networking-only problem. Foundational WSN literature identifies energy and communication as core limitations (Akyildiz et al., 2002; Anastasi et al., 2009), environmental deployments emphasize calibration and maintainability (Mainwaring et al., 2002; Corke et al., 2010), and urban IoT research shows the importance of interoperable gateways and service-oriented data access (Zanella et al.,

2014). The simulation-based prototype suggests that a dense low-power network can plausibly provide useful reliability, latency, and coverage for urban environmental intelligence. However, the numerical values should not be interpreted as real city measurements. A full empirical study should deploy nodes across multiple seasons, include regulatory or research-grade reference instruments, quantify sensor drift, document radio interference and vandalism risk, and evaluate maintenance cost per monitoring location. Additional work should compare ZigBee, LoRaWAN, cellular IoT, and hybrid communication strategies under the same urban conditions. Data governance also requires attention: environmental observations may be publicly valuable, but device location, infrastructure metadata, and administrative access should be protected through appropriate security and privacy controls (Malche et al., 2019; Toma et al., 2019). Overall, WSN-based monitoring is best positioned as a complementary layer to conventional environmental stations rather than a direct replacement. Dense low-cost nodes can reveal spatial patterns and provide early warnings, while reference stations provide traceable measurement quality. Combining these layers with cloud analytics and transparent quality flags can support evidence-based smart-city decisions in pollution management, heat-risk assessment, noise control, and water-resource protection. The proposed methodology offers a practical basis for such a field study using literature and technologies available through 2019. Several methodological limitations should be considered when the framework is transferred to a real city.

Low-cost air-quality and gas sensors can exhibit cross-sensitivity, humidity dependence, aging, and unit-to-unit variation; consequently, calibration coefficients estimated during a short co-location period may not remain stable for an entire season. Radio performance is also site-specific because buildings, foliage, traffic, and competing wireless systems alter link quality. For this reason, the field protocol should retain raw or minimally processed values, log firmware and calibration versions, and preserve node-health information so that apparent environmental changes can be distinguished from device faults. Environmental WSN research has repeatedly identified long-term maintenance and data quality as central deployment challenges (Hart & Martinez, 2006; Corke et al., 2010). Future validation should therefore use a phased deployment. A small calibration phase should first compare candidate nodes and communication technologies under controlled co-location. A second neighborhood-scale phase should test coverage, packet loss, power consumption, security, and maintenance workload under normal urban interference. Finally, a multi-zone phase should evaluate whether the increased spatial density produces decisions that could not be obtained from sparse reference stations alone. Success should be judged not merely by the number of connected devices, but by traceable measurement quality, sustained availability, interpretable alerts, and the ability of city stakeholders to act on the information. This staged approach follows the application-driven philosophy of early WSN deployments and the service-oriented integration expected in urban IoT systems (Mainwaring et al., 2002; Zanella et al., 2014).

## References

- Akyildiz, I. F., Su, W., Sankarasubramaniam, Y., & Cayirci, E. (2002). Wireless sensor networks: A survey. *Computer Networks*, 38(4), 393–422. [https://doi.org/10.1016/S1389-1286\(01\)00302-4](https://doi.org/10.1016/S1389-1286(01)00302-4)
- Anastasi, G., Conti, M., Di Francesco, M., & Passarella, A. (2009). Energy conservation in wireless sensor networks: A survey. *Ad Hoc Networks*, 7(3), 537–568. <https://doi.org/10.1016/j.adhoc.2008.06.003>
- Arroyo, P., Herrero, J. L., Suárez, J. I., & Lozano, J. (2019). Wireless sensor network combined with cloud computing for air quality monitoring. *Sensors*, 19(3), 691. <https://doi.org/10.3390/s19030691>
- Corke, P., Wark, T., Jurdak, R., Hu, W., Valencia, P., & Moore, D. (2010). Environmental wireless sensor networks. *Proceedings of the IEEE*, 98(11), 1903–1917. <https://doi.org/10.1109/JPROC.2010.2068530>
- Gubbi, J., Buyya, R., Marusic, S., & Palaniswami, M. (2013). Internet of Things (IoT): A vision, architectural elements, and future directions. *Future Generation Computer Systems*, 29(7), 1645–1660. <https://doi.org/10.1016/j.future.2013.01.010>
- Hancke, G. P., de Carvalho e Silva, B., & Hancke, G. P., Jr. (2013). The role of advanced sensing in smart cities. *Sensors*, 13(1), 393–425. <https://doi.org/10.3390/s130100393>
- Hart, J. K., & Martinez, K. (2006). Environmental sensor networks: A revolution in the earth system science? *Earth-Science Reviews*, 78(3–4), 177–191. <https://doi.org/10.1016/j.earscirev.2006.05.001>
- Malche, T., Maheshwary, P., & Kumar, R. (2019). Environmental monitoring system for smart city based on secure Internet of Things (IoT) architecture. *Wireless Personal Communications*, 107, 2143–2172. <https://doi.org/10.1007/s11277-019-06376-0>
- Raza, U., Kulkarni, P., & Sooriyabandara, M. (2017). Low power wide area networks: An overview. *IEEE Communications Surveys & Tutorials*, 19(2), 855–873. <https://doi.org/10.1109/COMST.2017.2652320>
- Toma, C., Alexandru, A., Popa, M., & Zamfiroiu, A. (2019). IoT solution for smart cities' pollution monitoring and the security challenges. *Sensors*, 19(15), 3401. <https://doi.org/10.3390/s19153401>
- Yick, J., Mukherjee, B., & Ghosal, D. (2008). Wireless sensor network survey. *Computer Networks*, 52(12), 2292–2330. <https://doi.org/10.1016/j.comnet.2008.04.002>
- Zanella, A., Bui, N., Castellani, A., Vangelista, L., & Zorzi, M. (2014). Internet of Things for smart cities. *IEEE Internet of Things Journal*, 1(1), 22–32. <https://doi.org/10.1109/JIOT.2014.2306328>